

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

| IDENTITY AND MANUFACTURER'S INFORMATION | | | | | | |
|--|--|---------------------------------------|--|---|-----------------|---------------------------|
| NFPA Rating: Health-2; Flammability-0; Reactivity-0; Special-- Manufactured For: Ascot Supply Corporation Address: 51 Hillwood Circle Address: Newnan, GA 30263-1088 | | | HMIS Rating: Health-2; Flammability-0; Reactivity-0; Personal Protection-B DOT Hazard Classification: ORM-D Identity (trade name as used on label): <p style="text-align: center;">PRE-BUFF CLEANER # 505-71216</p> | | | |
| Phone: 770-251-7330 EMERGENCY RESPONSE NUMBER: 1(800)255-3924 NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA | | | MSDS Number: A00365 Revision: 15 Date Prepared: 07/1/05 Prepared By: LF/DL/IB Information Calls: (770)422-2071 | | | |
| SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION | | | | | | |
| COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater) | | CAS Number | SARA III LIST | OSHA PEL (ppm) | ACGIH TLV (ppm) | Carcinogen Ref. Source ** |
| PERCHLOROETHYLENE | | 127-18-4 | Yes | 25 | 25 | a,b |
| ACETONE | | 67-64-1 | No | 1000 | 750 | d |
| CARBON DIOXIDE | | 124-38-9 | No | 5000 | 5000 | d |
| WARNING: This product contains a chemical or chemicals known to the State of California to cause cancer. | | | | | | |
| SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS | | | | | | |
| Boiling Point: N/A Vapor Pressure: PSIG @ 70°F (Aerosols): 85-100 Vapor Density (Air = 1): N/E Solubility in Water: Insoluble Appearance and Odor: Clear, colorless spray with chlorinated solvent odor. | | | Specific Gravity (H2O=1): Concentrate Only = 1.60 Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A Evaporation Rate (n-butyl acetate= 1): 2.1 (concentrate only) Water Reactive: No | | | |
| SECTION 3 - FIRE AND EXPLOSION HAZARD DATA | | | | | | |
| FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) NON-FLAMMABLE | | Auto Ignition Temperature: N/E | | Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E | | |
| FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. | | | EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide. | | | |
| Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture. | | | | | | |
| SECTION 4 - REACTIVITY HAZARD DATA | | | | | | |
| STABILITY [X] STABLE [] UNSTABLE | | | HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR | | | |
| Incompatibility (Mat. to avoid): Reactive metals, aluminum, magnesium, strong oxidizing agents. | | | Conditions to Avoid: Open flame, welding arcs, heat. | | | |
| Hazardous Decomposition Products: CO2, CO, HCl, small amounts of phosgene and chlorine. | | | | | | |
| SECTION 5 - HEALTH HAZARD DATA | | | | | | |
| PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS | | | | | | |
| ACUTE EFFECTS: Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness. Eye Contact: Irritation Skin Contact: Irritation due to defatting of skin. Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea. | | | | | | |
| CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause liver abnormalities, kidney, spleen, lung or brain damage, cardiac abnormalities. Perchloroethylene has been shown to increase the rate of spontaneously occurring malignant tumors in certain laboratory rats and mice. Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions. | | | | | | |
| EMERGENCY FIRST AID PROCEDURES | | | | | | |
| Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention. Skin Contact: Wash with soap and water. If irritated, seek medical attention. Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention. Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention. | | | | | | |
| SECTION 6 - CONTROL AND PROTECTIVE MEASURES | | | | | | |
| Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor. Protective Gloves: Neoprene gloves recommended. Eye Protection: Safety glasses recommended. Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV. Other Protective Clothing & Equipment: None Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing. | | | | | | |
| SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE | | | | | | |
| Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. Allow to evaporate if small spill. DO NOT FLUSH TO SEWER. Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard. Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F. Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid inhalation of vapors. | | | | | | |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

THIS MSDS IS CURRENT AS OF September 25, 2009. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at the manufacturer by these date codes and therefore must remain as the originating date.