

January 1,2007

#

## **MATERIAL SAFETY DATA SHEET**

### **SECTION I-NAME**

Product name as shown on label: Tire Slick Tire Mounting Lubricant  
Manufactures Name: Tire Slick, Inc.  
Address: 4811 East Fork Ln.  
Monroe, NC 28110  
Emergency Phone: 704-291-7171  
Contact Person: Mike Blessing

### **SECTION-II-INGREDIENTS**

This product contains no hazardous components as defined by the Occupational Safety and Health Administration Regular. (29CFR Section 1910.1200)

### **SECTION III PHYSICAL DATA**

Boiling Point: 212 F 100 C  
Vapor Pressure: @ 68°F 20°C OmmHG  
Percent Volatile By Volume (%): <95  
Omm Hg \_ psi  
Vapor Density (Air=1) NA  
Solubility in Water: Yes  
\*PH: 10.-11.5  
Odor: None  
Appearance:  
Blue Viscous Liquid, no odor  
\*PH will drop as product cures.

Specific Gravity: (H2O=1) 1  
Percent Solid by Weight:<5  
Evaporation Rate (H2O=1) 1  
Density: 1.0030@25C  
SSE Viscosity: 960

### **SECTION IV-HAZARDS**

Hazardous material description; proper shipping, hazard class, Hazard ID NONE  
NO (49CFR172.101)

Additional Hazards Classes: NONE

### **SECTION V-FIRST AID**

Effects of overexposure: None Known  
Conditions to avoid: None Known  
EXPOSURE  
FIRST AID PREVENTION

Inhalation  
Skin  
Eye  
Ingestion

Flush with clean water, if irritation persists see doctor  
SAFETY GOGGLES  
See Doctor

### **SECTION VI-FIRE FIGHTING**

Flash Point: Method used: Non-combustible

\_\_\_F \_\_\_C

Flammable limits:

\_\_\_LEL \_\_\_OEL

Extinguishing media: N/A

Unusual fire & explosion hazards: N/A

### **SECTION VII-HANDLING & STORAGE**

Steps to be taken when spilled:

Waste disposal method: Floors will be slippery, use care to avoid falling

Dispose of according to local regulations. Environmental friendly; Flush and rinse with water

Storage: No special requirements, avoid freezing as container may split

Precautions to be taken in handling & storage: None