



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

PREMA ULTRA FAST DRYING VULKANIZING CEMENT, FLAMMABLE

#### Art.-No.

PFC-4 (SKU No. 2205010); PFC-8 (SKU No. 2205020); PFC-32 (SKU No. 2205030); PIV-8FT (SKU No. 2205110); PFC 200 (SKU No.2205040); PFCO-25 (SKU No. 2245225)

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

adhesive

### 1.3. Details of the supplier of the safety data sheet

Company name: PREMA GmbH  
Street: Aspertscham 40  
Place: D-94081 Fürstentzell  
Telephone: +49 (0) 8502 917 150 0  
Responsible for the safety data sheet: sds@gbk-ingelheim.de

### 1.4. Emergency telephone

**number:** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24  
24

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Indications of danger: F - Highly flammable, Xi - Irritant, N - Dangerous for the environment

R phrases:

Highly flammable.

Irritating to skin.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Acute 1

Hazardous to the aquatic environment: Aquatic Chronic 1

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Very toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Hazardous components which must be listed on the label

n-Heptane

Acetone

Signal word:

Danger

Pictograms:

GHS02-GHS07-GHS09



**PREMA ULTRA FAST DRYING VULKANIZING CEMENT, FLAMMABLE**

00623-0001

**Hazard statements**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P273	Avoid release to the environment.

**2.3. Other hazards**

Vapours may form explosive mixture with air.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Preparation in organic solvents

**Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
205-563-8	n-Heptane	< 75 %
142-82-5	F - Highly flammable, Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R11-65-38-67-50-53	
601-008-00-2	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1 (M-Factor = 1); H225 H315 H336 H304 H400 H410	
01-2119457603-38		
200-662-2	Acetone	< 20 %
67-64-1	F - Highly flammable, Xi - Irritant R11-36-66-67	
606-001-00-8	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066	
01-2119471330-49		

Full text of R-, H- and EUH-phrases: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.  
Take away from danger area and lay down affected person.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours.  
Seek medical treatment immediately.

**After contact with skin**

Wash off with soap and plenty of water.  
Consult a doctor if skin irritation persists.

**After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical treatment by eye specialist.



#### **After ingestion**

Do not induce vomiting.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Causes serious eye irritation.

Causes skin irritation.

May cause drowsiness or dizziness.

Attention. Beware, danger of aspiration.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

---

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

##### **Unsuitable extinguishing media**

Full water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Fire may produce:

Carbon monoxide and carbon dioxide

#### **5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.

Protective suit.

#### **Additional information**

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

#### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

#### **6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

---

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Keep a good ventilation and air-exhaust at the place of work.

Avoid contact with skin, eyes and clothing.



**Advice on protection against fire and explosion**

Do not smoke - volatile.  
 Keep away from heat and sources of ignition.  
 Take precautionary measures against static discharges.  
 Use only explosion-proof equipment.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.  
 Pay attention to anti-explosion rules.

**Advice on storage compatibility**

Incompatible with oxidizing agents.

**Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

**7.3. Specific end use(s)**

adhesive

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
142-82-5	n-Heptane	500	2085		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

**8.2. Exposure controls**

**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Protective and hygiene measures**

Do not inhale vapours.  
 Wash hands before breaks and immediately after handling the product.  
 When using do not eat, drink or smoke.  
 Treat subsequently with skin cream.  
 Avoid contact with skin, eyes and clothing.  
 Remove and wash contaminated clothes before re-use.

**Eye/face protection**

Tightly fitting goggles (EN 166).  
 Eye wash bottle with pure water (EN 15154).

**Hand protection**

Splash protection:  
 Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0,7 mm, permeation resistance (wear duration) approx. 10 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.  
 This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.  
 Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Skin protection**

Solvent-resistant apron (EN 467).

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).



---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	Colourless, Milky	
Odour:	Hydrocarbon-like	
Initial boiling point and boiling range:	> 56 °C	
Flash point:	- 20 °C	
Lower explosion limits:	1,1 vol. %	
Upper explosion limits:	13,2 vol. %	
Vapour pressure: (at 20 °C)	233 hPa	*)
Density (at 20 °C):	0,7 g/cm <sup>3</sup>	
Water solubility: (at 20 °C)	Partially miscible	
Ignition temperature:	204 °C	
Viscosity / dynamic:	900 - 1200 mPa·s	
Viscosity / kinematic: (at 40 °C)	> 20,5 mm <sup>2</sup> /s	
Flow time: (at 23 °C)	> 10 min	3 DIN/ISO 2431
Solvent content:	89 - 91 %	

### 9.2. Other information

\*) Acetone

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No decomposition if stored and applied as directed.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

#### **Irritation and corrosivity**

Causes skin irritation.

Causes serious eye irritation.

#### **Sensitising effects**

Based on available data, the classification criteria are not met.



---

### STOT-single exposure

May cause drowsiness or dizziness. (n-Heptane ), (Acetone )

### Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

### Practical experience

#### Other observations

May cause irritation of the mucous membranes.

Effects of breathing high concentrations of vapour may include: Headache, dizziness, weakness, unconsciousness.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Contact with eyes may cause irritation.

Attention. Beware, danger of aspiration!

---

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecological data are not available.

Very toxic to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

### 12.6. Other adverse effects

Hazardous water pollutant.

### Further information

Do not flush into surface water or sanitary sewer system.

---

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

#### Waste disposal number of waste from residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances  
Classified as hazardous waste.

#### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

---

## SECTION 14: Transport information

### Land transport (ADR/RID)



**14.1. UN number:** UN1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L / 30 kg  
 Transport category: 2  
 Hazard No: 33  
 Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number:** UN1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L / 30 kg

**Marine transport (IMDG)**

**14.1. UN number:** UN1133  
**14.2. UN proper shipping name:** ADHESIVES (n-Heptane)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Marine pollutant: Yes  
 Limited quantity: 5 L / 30 kg  
 EmS: F-E; S-D

**Air transport (ICAO)**

**14.1. UN number:** UN1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Limited quantity Passenger: Y341 / 1 L

IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L



**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:                     yes



**14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

The transport takes place only in approved and appropriate packaging.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

1999/13/EC (VOC):                                     89 - 91 %

**National regulatory information**

Employment restrictions:                             Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information**

**Abbreviations and acronyms**

- ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
- RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
- ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
- IMDG = International Maritime Code for Dangerous Goods
- IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
- MARPOL = International Convention for the Prevention of Pollution from Ships
- IBC = Code International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
- CAS = Chemical Abstract Service
- EN = European norm
- ISO = International Organization for Standardization
- DIN = Deutsche Industrie Norm
- PBT = Persistent Bioaccumulative and Toxic

- LD = Lethal dose
- LC = Lethal concentration
- EC = Effect concentration
- IC = Median immobilisation concentration or median inhibitory concentration

**Relevant R-phrases (Number and full text)**

- 11             Highly flammable.
- 36             Irritating to eyes.
- 38             Irritating to skin.
- 50             Very toxic to aquatic organisms.
- 53             May cause long-term adverse effects in the aquatic environment.
- 65             Harmful: may cause lung damage if swallowed.
- 66             Repeated exposure may cause skin dryness or cracking.
- 67             Vapours may cause drowsiness and dizziness.

**Relevant H- and EUH-phrases (Number and full text)**

- H225             Highly flammable liquid and vapour.
- H304             May be fatal if swallowed and enters airways.
- H315             Causes skin irritation.





---

H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*