Material Safety Data Sheet



Truflex/Pang Bead and Repair Sealer

1. Product and company identification

Product name : Truflex/Pang Bead and Repair Sealer

Supplier : Same as manufacturer.

Trade name : Truflex/Pang Bead and Repair Sealer

Material uses : Other non-specified industry: Tire mounting sealant

Manufacturer : Tech International

200 East Coshocton Street

P.O. Box 486

Johnstown, Ohio 43031. www.techtirerepairs.com jsellers@techtirerepairs.com

 Code
 : B77F

 MSDS #
 : B77F

Validation date : 12/15/2011.

Print date : 12/15/2011.

Responsible name : Jeff Sellers

In case of emergency : Chemtrec 1-800-424-9300

Product type : Liquid.

2. Hazards identification

Physical state : Liquid. [Viscous liquid.]

Odor : Solvent. [Strong]

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Emergency overview : DANGER!

EXTREMELY FLAMMABLE LIQUID AND VAPOR. FLAMMABLE. VAPOR MAY CAUSE FLASH FIRE. CAUSES DIGESTIVE TRACT BURNS. MAY BE HARMFUL IF SWALLOWED. MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Extremely flammable liquid. Corrosive to the digestive tract. Causes burns. May be harmful if swallowed. Slightly irritating to the eyes, skin and respiratory system. Keep away from heat, sparks and flame. Do not breathe vapor or mist. Do not ingest. Do not get in eyes. Avoid contact with skin and clothing. May cause target organ damage, based on animal data. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation : Slightly irritating to the respiratory system.

Ingestion : Harmful if swallowed. Corrosive to the digestive tract. Causes burns.

Skin : Slightly irritating to the skin.

Eyes : Slightly irritating to the eyes.

Potential chronic health effects

Chronic effects: May cause target organ damage, based on animal data.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Hazards identification

Target organs

May cause damage to the following organs; central nervous system (CNS). Contains material which may cause damage to the following organs: cardiovascular

Over-exposure signs/symptoms

Inhalation

: Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion

: Adverse symptoms may include the following:

stomach pains

Skin

Adverse symptoms may include the following:

irritation redness

Eyes

: Adverse symptoms may include the following:

irritation watering redness

Medical conditions aggravated by over-

exposure

United States

: Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

Composition/information on ingredients 3.

Name solvent naphtha (petroleum b Rubber	olend), light				CAS nu 64742-8 9006-04	9-8	8	<mark>%</mark> 33 - 89 5.7
<u>Canada</u>								
Name solvent naphtha (petroleum b Rubber	olend), light				CAS nu 64742-89 9006-04	9-8	3	<mark>%</mark> 33 - 89 5.7
<u>Mexico</u>						Cla	assifi	<u>ication</u>
Name solvent naphtha (petroleum blend), light	CAS number 64742-89-8	UN number UN1993	<mark>%</mark> 83 - 89	IDLH -	<u>H</u> 2	E 3	R 0	<u>Special</u>
Rubber	9006-04-6	Not	5.7	-	0	0	0	

available.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact

Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation

Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

4. First aid measures

Ingestion

: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Notes to physician

: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product

: Extremely flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Extinguishing media

Suitable

: Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable

: Do not use water jet.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Hazardous thermal decomposition products

: No specific data.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Handling and storage

Handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits
solvent naphtha (petroleum blend), light	ACGIH TLV (United States). TWA: 400 ppm
Rubber	ACGIH TLV (United States, 2/2010). Absorbed through skin. Skin sensitizer. TWA: 0.001 mg/m³, (as total proteins) 8 hour(s). Form: Inhalable fraction. See Appendix C, paragraph A. Inhalable Particulate Mass TLVs (IPM–TLVs) for those materials that are hazardous when deposited anywhere in the respiratory tract.

Canada

Occupational exposure limits		TWA (8 hours)		STEL (15 mins)		Ceiling					
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
solvent naphtha (petroleum blend), light	US ACGIH	400	-	-	-	-	-	-	-	_	
Rubber , as total proteins	US ACGIH 2/2010	-	0.001	-	-	-	-	-	-	-	[1][3] [a]
	AB 4/2009	-	0.001	-	-	-	-	-	-	-	[1]
Rubber	BC 10/2009	-	0.0001	-	-	-	-	-	-	-	[1][3] [b]
Rubber , Inhalable allergenic proteins	ON 7/2010	-	0.0001	_	-	-	-	-	1		[1][3] [a]

[1]Absorbed through skin. [3]Skin sensitization

Form: [a]Inhalable fraction. See Appendix C, paragraph A. Inhalable Particulate Mass TLVs (IPM–TLVs) for those materials that are hazardous when deposited anywhere in the respiratory tract. [b]Inhalable allergenic proteins

<u>Mexico</u>

Ingredient	Exposure limits

8. Exposure controls/personal protection

solvent naphtha (petroleum blend), light

Rubber

ACGIH TLV (United States).

TWA: 400 ppm

ACGIH TLV (United States, 2/2010). Absorbed through skin. Skin sensitizer.

TWA: 0.001 mg/m³, (as total proteins) 8 hour(s). Form: Inhalable fraction. See Appendix C, paragraph A. Inhalable Particulate Mass TLVs (IPM–TLVs) for those materials that are hazardous when deposited anywhere in the respiratory tract.

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Physical and chemical properties

Physical state : Liquid. [Viscous liquid.]

Flash point : Closed cup: -6.7°C (19.9°F)

Flammable limits : Lower: 1.3%

Upper: 8%

Color : Black.

Odor : Solvent. [Strong]

Boiling/condensation point: 98.3 to 110°C (208.9 to 230°F)

Relative density : 0.76

Vapor pressure : 14.7 kPa (110.5 mm Hg) [20°C]

Vapor density : >1 [Air = 1]

Volatility : 89.1% (v/v), 89.1% (w/w)

12/15/2011. B77F **5/11**

Physical and chemical properties 9.

: >1 (butyl acetate = 1) **Evaporation rate**

Stability and reactivity

Chemical stability

: The product is stable.

Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not

allow vapor to accumulate in low or confined areas.

Materials to avoid

Highly reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Toxicological information 11.

United States

Acute toxicity

Product/ingredient name Result **Species** Dose **Exposure**

solvent naphtha (petroleum blend), light LD50 Oral Rat 2000 mg/kg

Conclusion/Summary

Chronic toxicity

: Not available.

Conclusion/Summary : Not available.

Irritation/Corrosion

Conclusion/Summary : Not available.

Sensitizer

Conclusion/Summary

Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Canada

Acute toxicity

Product/ingredient name Result **Species** Dose **Exposure**

solvent naphtha (petroleum blend), light LD50 Oral Rat 2000 mg/kg

Conclusion/Summary

Chronic toxicity

: Not available.

Conclusion/Summary

: Not available.

Irritation/Corrosion

Conclusion/Summary : Not available.

Sensitizer

Conclusion/Summary Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Mutagenicity

12/15/2011. 6/11 B77F

11. Toxicological information

Conclusion/Summary

: Not available.

Teratogenicity

Conclusion/Summary

: Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

Mexico

Acute toxicity

Product/ingredient name Result Species Dose Exposure

solvent naphtha (petroleum blend), light LD50 Oral Rat 2000 mg/kg -

Conclusion/Summary

nmary : Not available.

Chronic toxicity

Conclusion/Summary: Not available.

<u>Irritation/Corrosion</u>

Conclusion/Summary: Not available.

Sensitizer

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

United States

Aquatic ecotoxicity

Conclusion/Summary: Not available.

Persistence/degradability

Conclusion/Summary: Not available.

Canada

Aquatic ecotoxicity

Conclusion/Summary: Not available.

Persistence/degradability

Conclusion/Summary: Not available.

<u>Mexico</u>

Aquatic ecotoxicity

Conclusion/Summary: Not available.

Persistence/degradability

Conclusion/Summary: Not available.

13. Disposal considerations

Waste disposal

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	1133	Adhesives	3	II	FLAMMARIE LIZUP	-
TDG Classification	1133	Adhesive.	3	II		-
Mexico Classification	1133	Adhesive.	3	II	<u>*</u>	-
ADR/RID Class	1133	Adhesive.	3	II	<u>₹</u>	
IMDG Class	1133	Adhesive	3	II	<u>₹</u>	-
IATA-DGR Class	1133	Adhesive	3	II	**************************************	-

PG*: Packing group

15. Regulatory information

United States

HCS Classification : Flammable liquid

Corrosive material Target organ effects

U.S. Federal regulations

: TSCA 8(a) IUR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): Not determined.

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: solvent naphtha (petroleum blend), light SARA 311/312 MSDS distribution - chemical inventory - hazard identification: No products were found.

products were found.

Clean Air Act (CAA) 112 accidental release prevention: No products were found.

State regulations

: Connecticut Carcinogen Reporting: None of the components are listed.

Connecticut Hazardous Material Survey: None of the components are listed.

Florida substances: None of the components are listed.

Illinois Chemical Safety Act: None of the components are listed.

Illinois Toxic Substances Disclosure to Employee Act: None of the components are

listed.

Louisiana Reporting: None of the components are listed. Louisiana Spill: None of the components are listed. Massachusetts Spill: None of the components are listed.

Massachusetts Substances: None of the components are listed. **Michigan Critical Material**: None of the components are listed.

Minnesota Hazardous Substances: None of the components are listed. **New Jersey Hazardous Substances**: None of the components are listed.

New Jersey Spill: None of the components are listed.

New Jersey Toxic Catastrophe Prevention Act: None of the components are listed. New York Acutely Hazardous Substances: None of the components are listed. New York Toxic Chemical Release Reporting: None of the components are listed. Pennsylvania RTK Hazardous Substances: None of the components are listed. Rhode Island Hazardous Substances: None of the components are listed.

United States inventory

(TSCA 8b)

: Not determined.

<u>Canada</u>

WHMIS (Canada)

Canadian lists

: Class B-2: Flammable liquid

: CEPA Toxic substances: None of the components are listed.

Canadian ARET: None of the components are listed.

Canadian NPRI: The following components are listed: Solvent naphtha light aliphatic

Alberta Designated Substances: None of the components are listed. Ontario Designated Substances: None of the components are listed. Quebec Designated Substances: None of the components are listed.

Canada inventory

: Not determined.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Mexico

Classification



GHS Classification

15. Regulatory information

Hazard symbol or symbols







Precautionary statements

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Wear protective gloves. Wear eye or face protection. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Keep cool. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazard statements

: Highly flammable liquid and vapor.

Harmful if swallowed.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

EU regulations

Hazard symbol or symbols



Risk phrases

: R11- Highly flammable.

R42- May cause sensitization by inhalation.

Safety phrases

: S2- Keep out of the reach of children.

S23- Do not breathe [***].

S45- In case of accident or if you feel unwell, seek medical advice immediately (show the

label where possible).

S63- In case of accident by inhalation: remove casualty to fresh air and keep at rest.

International regulations

International lists : Australia inventory (AICS): Not determined.

China inventory (IECSC): Not determined.

Japan inventory: Not determined. **Korea inventory**: Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

16. Other information

Label requirements

EXTREMELY FLAMMABLE LIQUID AND VAPOR. FLAMMABLE. VAPOR MAY CAUSE FLASH FIRE. CAUSES DIGESTIVE TRACT BURNS. MAY BE HARMFUL IF SWALLOWED. MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health 1 0 Instability/Reactivity
Special

 Date of printing
 : 12/15/2011.

 Date of issue
 : 12/15/2011.

 Version
 : 0.03

Indicates information that has changed from previously issued version. Indicates information that has changed from previously issued version.

Notice to reader

16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.