Material Safety Data Sheet E841 BTPTM Professional



12/29/05

Exposure Limits

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

BTPTM Professional Stoner Incorporated Product Name: 1070 Robert Fulton Hwy. Product Code: E841

Version Date: 1-800-424-9300 [CHEMTREC] 1-800-227-5538 24-hour emergency phone:

2. COMPOSITION / INFORMATION ON INGREDIENTS

ACGIH TLV **COMPONENT** OSHA PEL OTHER Water 7732-18-5 None established None established None established Aqueous organic emulsion Mixture None established None established None established Aqueous carbon black dispersion 1333-86-4 None established None established None established 5 mg/m3 NJ Trade Secret Registry #80100382-5097P 10 mg/m3 None established Nonionic surfactant 9016-45-9 None established None established None established

3. HAZARDS IDENTIFICATION

Ouarryville, PA 17566

POTENTIAL ACUTE [single or short term] HEALTH EFFECTS OF OVEREXPOSURE

Eye: May cause eye irritation. Skin: May cause skin irritation.

Ingestion: No hazard in normal industrial use. No evidence of harmful effects from available information.

Inhalation: Inhalation can cause nose, throat, and respiratory tract irritation, coughing and headache. Inhalation may cause irritation of the upper

respiratory passages.

POTENTIAL CHRONIC [long term] HEALTH EFFECTS OF OVEREXPOSURE:

General Effects: No chronic health effects known. Prolonged overexposure to any nuisance dust may cause lung injury. Symptoms include

coughing, shortness of breath, and reduced pulmonary function.

Cancer Information: THIS PRODUCT CONTAINS NO COMPONENTS LISTED AS CARCINOGENIC BY IARC, NTP, OR OSHA 1910(Z) No

data

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

Respiratory related chronic illnesses (i.e. asthma, etc.).

HAZARDOUS WARNINGS HMIS:

Health: 1 Flammability: 0 Reactivity: 0 Personal Protective Equipment See Section 8

FIRST AID MEASURES

Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is Eyes:

visual difficulty, seek medical attention.

Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Remove contaminated clothing.

Seek medical attention if symptoms persist. Wash clothing before reuse.

Do not induce vomiting. Have victim drink 8 to 10 ounces of water to dilute the material in the stomach. Obtain medical attention Ingestion:

immediately. Contact a physician, medical facility, or poison control center for advise on whether to induce vomiting.

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Inhalation:

NOTES TO PHYSICIAN:

No additional first aid information available.

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: Material can splatter above 212F. Dried product can burn.

Fire Fighting Instructions: Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus.

Use water spray, foam, dry chemical, or CO2. water, carbon dioxide, dry chemical, dry powder

300.0 deg. F TCC Flash Point: Lower Flammability Limit: Not applicable %

Upper Flammability Limit: Not applicable % Autoignition Temperature: Not applicable deg. F

Material Safety Data Sheet E841 BTPTM Professional



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc., product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Wear appropriate personal protective equipment (PPE). Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. If runoff occurs, notify authorities as required. Remove all sources of ignition. Wear appropriate clothing. Stop or reduce discharge if it can be done safely. Ventilate contaminated area.

7. HANDLING AND STORAGE

Handling: Use with adequate ventilation. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor.

Storage: Keep from freezing, Keep from freezing. Store in a cool, dry, well ventilated area away from all sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: No exposure limits exist for the constituents of this product. General room ventilation might be required to maintain

operator comfort under normal conditions of use.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such

as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid,

or airborne material. Do not wear contact lenses. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact

with skin

Respiratory Protection: None required for well ventilated situations. Use NIOSH approved respirator where there is likelihood of inhalation of the

product mist, spray or aerosol.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Bulk liquid Vapor Density: [air = 1] 0.04

Appearance: Black Evaporation Rate: <0.020 (n-Butyl acetate = 1)

Odor:SlightSolubility in Water:Complete; 100%Specific Gravity:1 @ 70 deg FBoiling Point:212 deg FVapor Pressure:0.0 mmHg @ 70 deg FpH:Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability: Stable. Conditions to Avoid: None.

Decomposition Products: Acrylic Polymers

11. DISPOSAL CONSIDERATIONS

Disposal: Dispose according to Federal, State and local regulations.

12. TRANSPORTATION INFORMATION

DOT Name: Not regulated by DOT UN Number: Not regulated by DOT IATA Name: Not regulated by DOT Hazardous Class: Not regulated by DOT Packing Group: Not regulated by DOT

13. REGULARTORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT CAS # % BY WEIGHT Regulatory Body
No components listed in this section. SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.

Ethylene oxide 75-21-8 0.001- 0.01 Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.

Ethylene oxide 75-21-8 0.001- 0.01 Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Incorporated, it is the user's obligation to determine the conditions of safe use.