

VENDOR # 1958
1957

PART# MPL55
MPL5

Material Safety Data Sheet

Murphy's Concentrated Extra Slippery Tire Mounting Compound Preparation: Aug 2000 / Revised: July 2010

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Murphy's Concentrated Extra Slippery Tire Mounting Compound
Chemical Formula: 96-4B2
Manufacturer: JTM Products, Inc., 31025 Carter Street, Solon, OH 44139, Phone (440) 287-2302, FAX (440) 287-3095(CHEM-TEL 24-hour emergency: (800) 255-3924)

Section 2 - Composition / Information on Ingredients

Blend of polymers, water and rust inhibitors containing (slight irritants) =
Poly(oxy-1,2-ethanediyl), alpha (nonylphenol)-, omega, -hydroxy- CAS# 009016-45-9 up to 0.5% by weight
Ethanol, 2,2',2"-nitrioltris- CAS# 000102-71-6 up to 0.3% by weight.
Dipropylene glycol CAS# 25265-71-8 up to 0.14% by weight
1-(3-chloroallyl)-3,5,7-Triaza-1-azoniaadamantane CAS# 004080-31-3 up to 0.11% by weight

Section 3 - Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Potential Health Effects

Primary Entry Routes: Not Hazardous
Carcinogenicity: IARC, NTP, and OSHA do not list the ingredients in Murphy's Concentrated Extra Slippery Tire Mounting Compound as a carcinogen.


HMIS	
H	1
F	0
R	0
PPE†	
†Sec. 8	

Section 4 - First Aid Measures

Eye Contact: Flush with copious volumes of water for 15 minutes while holding eyelids open.
Skin Contact: Wash with water. *If irritation persists, call a physician.*

Section 5 - Fire-Fighting Measures

Flash Point: >220 °F (>104 °C) **LEL:** NA
Flash Point Method: NA, contains water **UEL:** NA
Autoignition Temperature: NA **Flammability Classification:** 0
Extinguishing Media: Water, water fog, alcohol foam, carbon dioxide or dry chemical are all suitable.
Unusual Fire or Explosion Hazards: None
Hazardous Combustion Products: None
Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.
Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.



Section 6 - Accidental Release Measures

Spill /Leak Procedures: This product is a water soluble polymer.
Containment: For large spills, dike far ahead of liquid spill for later disposal.
Cleanup: Place the bulk of any spilled material into drums, then rinse any remaining material to sewage treatment facility, in accordance with any applicable regulations.
Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: No special precautions are required.
Storage Requirements: No special precautions are required.
Regulatory Requirements: No known regulatory requirement for handling and storage.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls: Ventilation: Provide general or local exhaust ventilation systems.
Administrative Controls:
Respiratory Protection: If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Murphy's Concentrated Extra Slippery Tire Mounting Compound

Protective Clothing/Equipment: Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations, safety/quickdrench showers, and washing facilities available in work area.

Contaminated Equipment: Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State: Liquid	pH: 9.0-10.5
Appearance and Odor: blue, clear liquid with bland odor	Water Solubility: complete solubility in water
Odor Threshold: NA	Boiling Point: >220 °F
Vapor Pressure: NA	Freezing/Melting Point: 32 °F
Vapor Density (Air=1): NA	Viscosity: 4000 cps
Formula Weight: NA (blend)	Refractive Index: unknown
Density: 8.4 lbs./gal.	Surface Tension: unknown
Specific Gravity (H₂O=1, at 4 °C): 1.0	% Volatile: 95
	Evaporation Rate: NA

Section 10 - Stability and Reactivity

Stability: Murphy's Concentrated Extra Slippery Tire Mounting Compound is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization will not occur.

Chemical Incompatibilities:

Conditions to Avoid: Also avoid contact with strong oxidizing agents.

Hazardous Decomposition Products: Thermal oxidative decomposition of Murphy's Concentrated Extra Slippery Tire Mounting Compound can produce oxides of carbon and nitrogen.

Section 11- Toxicological Information

Toxicity Data:

Eye Effects: Eye irritant.

Skin Effects: Slight skin irritant if allowed to remain in contact.

Section 12 - Ecological Information

Ecotoxicity: Environmental Fate

Environmental Transport: Unknown. **Environmental Degradation:** Unknown. **Soil Absorption/Mobility:** Unknown.

Section 13 - Disposal Considerations

Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Section 14 - Transport Information

Not hazardous under DOT regulations.

Section 15 - Regulatory Information

EPA Regulations: None apply.

Section 16 - Other Information

Prepared By: B. Noragon

Approved By: B. Roll

Disclaimer: JTM PRODUCTS, INC. makes no warranty, expressed or implied, as to the accuracy, completeness, or reliability of information contained herein, except that such information is, to the best of JTM's knowledge and belief, accurate as of the date indicated. It is for the purchaser and/or user to decide whether this information is suitable for his purposes.

REVISED March 2005/John Cahoon (section 1, 2 and 9) Revised July 2010 D. Barrer (section 2)

Material Safety Data Sheet

PART# MPL1

Murphy's Liquid Tire Mounting Compound

Date of Preparation: August 2000/Revised April 2010

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Murphy's Liquid Tire Mounting Compound

Chemical Formula: 88-8LS

Manufacturer: JTM Products, Inc., 31025 Carter Street, Solon, OH 44139, Phone (440) 287-2302, FAX (440) 287-3095
(CHEM-TEL 24-hour emergency: (800) 255-3924)

Section 2 - Composition / Information on Ingredients

Blend of soap, water and rust inhibitors.

May contain up to 0.06% by wt. Monoisopropanolamine CAS #78-96-6 (revised April 2010/D. Barrer)

Section 3 - Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Potential Health Effects

Primary Entry Routes: Not Hazardous

Carcinogenicity: IARC, NTP, and OSHA do not list the ingredients in Murphy's Liquid Tire Mounting Compound as carcinogens.

HMIS
H 1
F 0
R 0
PPE†
†Sec. 8

Section 4 - First Aid Measures

Eye Contact: Flush with copious volumes of water for 15 minutes while holding eyelids open.

Skin Contact: Wash with water.

If irritation persists, call a physician.

Section 5 - Fire-Fighting Measures

Flash Point: >220 °F (>104 °C)

LEL: NA

Flash Point Method: NA, contains water

UEL: NA

Autoignition Temperature: NA

Flammability Classification: 0


Extinguishing Media: Water, water fog, alcohol foam, carbon dioxide or dry chemical are all suitable.

Unusual Fire or Explosion Hazards: None

Hazardous Combustion Products: None

Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.



Section 6 - Accidental Release Measures

Spill /Leak Procedures: This product is a biodegradable soap.

Containment: For large spills, dike far ahead of liquid spill for later disposal.

Cleanup: Place the bulk of any spilled material into drums, then rinse any remaining material to sewage treatment facility, in accordance with any applicable regulations.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: No special precautions are required.

Storage Requirements: No special precautions are required.

Regulatory Requirements: No known regulatory requirement for handling and storage.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems.

Administrative Controls:

Respiratory Protection: If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Murphy's Liquid Tire Mounting Compound

Protective Clothing/Equipment: Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State: Liquid	pH: 11.0-12.0
Appearance and Odor: amber, viscous liquid with bland odor	Water Solubility: complete solubility in water
Odor Threshold: NA	Boiling Point: >220 °F
Vapor Pressure: NA	Freezing/Melting Point: <32 °F
Vapor Density (Air=1): NA	Viscosity: > 100 cps
Formula Weight: NA (blend)	Refractive Index: unknown
Density: 8.5 lbs./gal.	Surface Tension: unknown
Specific Gravity (H₂O=1, at 4 °C): 1.02	% Volatile: >80
	Evaporation Rate: NA

Section 10 - Stability and Reactivity

Stability: Murphy's Liquid Tire Mounting Compound is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization will not occur.

Chemical Incompatibilities:

Conditions to Avoid: Reactive alloys such as aluminum, brass, bronze. Also avoid contact with strong oxidizing agents.

Hazardous Decomposition Products: Thermal oxidative decomposition of Murphy's Liquid Tire Mounting Compound can produce oxides of carbon and nitrogen.

Section 11 - Toxicological Information

Toxicity Data:

Eye Effects: Eye irritant.

Skin Effects: Slight skin irritant if allowed to remain in contact.

Section 12 - Ecological Information

Ecotoxicity: Environmental Fate

Environmental Transport: Unknown.

Environmental Degradation: Soaps are well known to be biodegradable.

Soil Absorption/Mobility: Unknown.

Section 13 - Disposal Considerations

Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Section 14 - Transport Information

Not hazardous under DOT regulations.

Section 15 - Regulatory Information

EPA Regulations: None apply. All ingredients are listed on the TSCA inventory.

Section 16 - Other Information

Prepared By: B. Noragon

Approved By: B. Roll

Disclaimer: JTM PRODUCTS, INC. makes no warranty, expressed or implied, as to the accuracy, completeness, or reliability of information contained herein, except that such information is, to the best of JTM's knowledge and belief, accurate as of the date indicated. It is for the purchaser and/or user to decide whether this information is suitable for his purposes.

Section 2 & 15, Revised 4/2010, D. Barrer