

Version 1.1	Revision Date: 03/03/2015		SDS Number: 6483-00002	Date of last issue: 02/26/2015 Date of first issue: 02/26/2015	
SECTION	1. IDENTIFICATION				
Product name		:	: GOJO® SUPRO MAX™ Hand Cleaner		
	afacturer or supplier's	det			
Comp	pany name of supplier	:	GOJO Industries, Inc.		
Addre	Address		One GOJO Plaza, Suite 500 Akron OH 44311		
Telep	hone	:	1 (330) 255-6000		
Emer	Emergency telephone		1-800-424-9300 CHEMTREC		
Reco	mmended use of the o	cher	nical and restriction	ons on use	
Reco	mmended use	:	Skin-care		
Restrictions on use		:	consumers and o foreseeable use. specifically define exempt from the While this materia contains valuable proper use of the as well as unusua spills. This SDS s employees and o intended-use guid	I care or cosmetic product that is safe for ther users under normal and reasonably Cosmetics and consumer products, ed by regulations around the world, are requirement of an SDS for the consumer. al is not considered hazardous, this SDS e information critical to the safe handling and product for industrial workplace conditions al and unintended exposures such as large should be retained and available for ther users of this product. For specific dance, please refer to the information package or instruction sheet.	

### SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Serious eye damage	: Category 1
GHS Label element Hazard pictograms	
Signal Word	: Danger
Hazard Statements	: H318 Causes serious eye damage.
Precautionary Statements	: <b>Prevention:</b> P280 Wear eye protection/ face protection. <b>Response:</b>



Version 1.1	Revision Date: 03/03/2015	MSDS Number: 66483-00002	Date of last issue: 02/26/2015 Date of first issue: 02/26/2015
		water for sever	P338 + P310 IF IN EYES: Rinse cautiously with al minutes. Remove contact lenses, if present . Continue rinsing. Immediately call a POISON ctor/ physician.
Othe	r hazards		
None	known.		

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Distillates (petroleum), hydrotreated light	64742-47-8	>= 10 - < 20
Alcohols, C10-16, ethoxylated, sulfates, sodium salts	68585-34-2	>= 5 - < 10
Cocoamidopropyl betaine	61789-40-0	>= 1 - < 5
Titanium dioxide	13463-67-7	>= 1 - < 5
5-Chloro-2-methyl-4-isothiazolin-3-one	26172-55-4	< 0.1

#### **SECTION 4. FIRST AID MEASURES**

General advice	In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.	
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.	
In case of skin contact	: Wash with water and soap as a precaution. Get medical attention if symptoms occur.	
In case of eye contact	<ul> <li>In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.</li> <li>If easy to do, remove contact lens, if worn.</li> <li>Get medical attention immediately.</li> </ul>	
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.	
Most important symptoms and effects, both acute and delayed	: Causes serious eye damage.	
Protection of first-aiders	: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.	
Notes to physician	: Treat symptomatically and supportively.	



Version	Revision Date:	MSDS Number:	Date of last issue: 02/26/2015	
1.1	03/03/2015	66483-00002	Date of first issue: 02/26/2015	

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Dry chemical Carbon dioxide (CO2)
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion prod- ucts	:	Carbon oxides Sulfur oxides Metal oxides Nitrogen oxides (NOx) Chlorine compounds
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.	
Environmental precautions	Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or o barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.	il
Methods and materials for containment and cleaning up	Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked materia can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items	



Version 1.1	Revision Date: 03/03/2015	MSDS Number: 66483-00002	Date of last issue: 02/26/2015 Date of first issue: 02/26/2015
		employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.	
SECTION	N 7. HANDLING AND ST	ORAGE	
Tech	nnical measures		ng measures under EXPOSURE ERSONAL PROTECTION section.
Loca	al/Total ventilation	: Use only with a	adequate ventilation.
Advice on safe handling		Do not swallov Do not get in e Avoid prolonge Handle in acco practice. Keep containe	
Con	ditions for safe storage	Keep tightly clo	ly labeled containers. osed. dance with the particular national regulations.
Mate	erials to avoid	: Do not store w Strong oxidizin	ith the following product types: ng agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH

### Hazardous components without workplace control parameters

Ingredients	CAS-No.
Alcohols, C10-16, ethoxylated,	68585-34-2
sulfates, sodium salts	
Cocoamidopropyl betaine	61789-40-0
5-Chloro-2-methyl-4-	26172-55-4



## **GOJO® SUPRO MAX™ Hand Cleaner**

Version 1.1	Revision Date: 03/03/2015	MSDS Number: 66483-00002	Date of last issue: 02/26/2015 Date of first issue: 02/26/2015
isothia	azolin-3-one		
Engir	neering measures	Minimize workp Dust formation product. In add limitations of co workplaces hav assessment. Re Particulates No dust, 5 mg/m3 Particles (insolu	te ventilation, especially in confined areas. Nace exposure concentrations. may be relevant in the processing of this ition to substance-specific OELs, general oncentrations of particulates in the air at re to be considered in workplace risk elevant limits include: OSHA PEL for t Otherwise Regulated of 15 mg/m3 - total - respirable fraction; and ACGIH TWA for uble or poorly soluble) Not Otherwise ng/m3 - respirable particles, 10 mg/m3 - les.
Perso	onal protective equipn	nent	
Respi	iratory protection	maintain vapor concentrations unknown, appro Follow OSHA re use NIOSH/MS by air purifying hazardous cher supplied respira release, exposu	cal exhaust ventilation is recommended to exposures below recommended limits. Where are above recommended limits or are opriate respiratory protection should be worn. espirator regulations (29 CFR 1910.134) and HA approved respirators. Protection provided respirators against exposure to any mical is limited. Use a positive pressure air ator if there is any potential for uncontrolled ure levels are unknown, or any other there air purifying respirators may not provide ction.
	protection terial	: Impervious glov	ves
Re	marks	on the concentr time is not dete For special app resistance to ch gloves with the	to protect hands against chemicals depending ration specific to place of work. Breakthrough rmined for the product. Change gloves often! lications, we recommend clarifying the nemicals of the aforementioned protective glove manufacturer. Wash hands before he end of workday.
Eye p	rotection	Chemical resist	ring personal protective equipment: ant goggles must be worn. likely to occur, wear:
Skin a	and body protection	resistance data potential. Skin contact mu	ate protective clothing based on chemical and an assessment of the local exposure ust be avoided by using impervious protective a, aprons, boots, etc).
Hygie	ne measures	located close to	e flushing systems and safety showers are the working place. not eat, drink or smoke.



Version 1.1	Revision Date: 03/03/2015		DS Number: 183-00002	Date of last issue: 02/26/2015 Date of first issue: 02/26/2015
			Wash contamin	ated clothing before re-use.
SECTION	9. PHYSICAL AND CH	ЕМІС	CAL PROPERTI	ES
Appe	arance	:	liquid	
Color		:	tan, opaque	
Odor		:	pleasant	
Odor	Threshold	:	No data availal	ble
рН		:	4.5 - 8.0	
Meltir	ng point/freezing point	:	No data availal	ble
Solidi	fication / Setting point		13.7 °C	
Initial range	boiling point and boiling	:	97 °C	
Flash	Flash point		> 100 °C	
Evaporation rate		:	No data availal	ble
Flammability (solid, gas)		:	Not applicable	
Uppe	r explosion limit	:	No data availal	ble
Lowe	r explosion limit	:	No data availal	ble
Vapo	Vapor pressure		No data availal	ble
Relati	ive vapor density	:	No data availal	ble
Densi	ity	:	1.00 g/cm3	
	ility(ies) ater solubility	:	soluble	
	ion coefficient: n- ol/water	:	Not applicable	
Autoignition temperature		:	No data availal	ble
Decomposition temperature		:	The substance	or mixture is not classified self-reactive.
Visco Vis	sity cosity, kinematic	:	12,000 - 40,00	0 mm2/s (20 °C)
Explo	sive properties	:	Not explosive	
Oxidiz	zing properties	:	The substance	or mixture is not classified as oxidizing.



Version	Revision Date:	MSDS Number:	Date of last issue: 02/26/2015
1.1	03/03/2015	66483-00002	Date of first issue: 02/26/2015

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reac- tions	: Can react with strong oxidizing agents.
Conditions to avoid	: None known.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation	
Skin contact	
Ingestion	
Eye contact	

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg
		Method: Calculation method

#### Ingredients:

Distillates (petroleum), hydro Acute oral toxicity	p <b>treated light:</b> : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	<ul> <li>LC50 (Rat): &gt; 5.3 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials</li> </ul>
Acute dermal toxicity	<ul> <li>LD50 (Rabbit): &gt; 3,160 mg/kg Assessment: The substance or mixture has no acute dermal toxicity</li> </ul>
Alcohols, C10-16, ethoxylate	
Acute oral toxicity	<ul> <li>LD50 (Rat): &gt; 2,000 mg/kg</li> <li>Assessment: The substance or mixture has no acute oral</li> </ul>

### Cocoamidopropyl betaine:

toxicity



## **GOJO® SUPRO MAX™ Hand Cleaner**

Version 1.1	Revision Date: 03/03/2015	MSDS Number: 66483-00002	Date of last issue: 02/26/2015 Date of first issue: 02/26/2015		
Acute	e oral toxicity	Method: OECD	<ul> <li>LD50: &gt; 5,000 mg/kg</li> <li>Method: OECD Test Guideline 401</li> <li>Remarks: Based on data from similar materials</li> </ul>		
Acute	e dermal toxicity	Assessment: Th toxicity	,000 mg/kg Test Guideline 402 ne substance or mixture has no acute dermal d on data from similar materials		
	ium dioxide:		000 malles		
Acute	e oral toxicity	: LD50 (Rat): > 5	,000 mg/kg		
Acute	inhalation toxicity	: LC50 (Rat): > 6 Exposure time: Test atmospher Assessment: Th inhalation toxici	4 h e: dust/mist ne substance or mixture has no acute		
5-Ch	loro-2-methyl-4-isothi	azolin-3-one:			
	e oral toxicity	: Acute toxicity es Method: Expert	stimate: 100 mg/kg judgment d on data from similar materials		
Acute	inhalation toxicity	: LC50 (Rat): 0.3 Exposure time: Test atmospher Remarks: Base	4 h		
Acute	e dermal toxicity	Method: Expert	stimate: 300 mg/kg judgment d on data from similar materials		
Skin	corrosion/irritation				
Not c	lassified based on avai	lable information.			

#### Product:

Result: No skin irritation

#### Ingredients:

**Distillates (petroleum), hydrotreated light:** Assessment: Repeated exposure may cause skin dryness or cracking.

#### Alcohols, C10-16, ethoxylated, sulfates, sodium salts:

Result: Skin irritation

### Titanium dioxide:

Species: Rabbit Result: No skin irritation

#### 5-Chloro-2-methyl-4-isothiazolin-3-one:

Result: Corrosive after 3 minutes to 1 hour of exposure Remarks: Based on data from similar materials



Version	Revision Date:	MSDS Number:
1.1	03/03/2015	66483-00002

Date of last issue: 02/26/2015 Date of first issue: 02/26/2015

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Ingredients:

#### **Distillates (petroleum), hydrotreated light:** Species: Rabbit Result: No eye irritation

#### Alcohols, C10-16, ethoxylated, sulfates, sodium salts: Result: Irreversible effects on the eye

#### Cocoamidopropyl betaine:

Species: Rabbit Result: Irreversible effects on the eye Method: OECD Test Guideline 405 Remarks: Based on data from similar materials

#### Titanium dioxide:

Species: Rabbit Result: No eye irritation

#### 5-Chloro-2-methyl-4-isothiazolin-3-one:

Result: Irreversible effects on the eye Remarks: Based on data from similar materials

#### Respiratory or skin sensitization

Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

#### Product:

Assessment: Does not cause skin sensitization.

#### Ingredients:

#### Distillates (petroleum), hydrotreated light:

Test Type: Maximization Test (GPMT) Routes of exposure: Skin contact Species: Guinea pig Result: negative Remarks: Based on data from similar materials

#### Cocoamidopropyl betaine:

Test Type: Maximization Test (GPMT) Routes of exposure: Skin contact Species: Guinea pig Result: negative Remarks: Based on data from similar materials

#### Titanium dioxide:

Test Type: Local lymph node assay (LLNA) Routes of exposure: Skin contact Species: Mouse Result: negative

#### 5-Chloro-2-methyl-4-isothiazolin-3-one:



## **GOJO® SUPRO MAX™ Hand Cleaner**

rsion	Revision Date: 03/03/2015	MSDS Number 66483-00002	Date of last issue: 02/26/2015 Date of first issue: 02/26/2015
Resul	es of exposure: Skin cor t: positive ırks: Based on data fror		s
Asses	ssment: Probability or e	vidence of skin s	ensitization in humans
	cell mutagenicity assified based on availa	able information.	
Inare	dients:		
Distill	lates (petroleum), hyd toxicity in vitro	-	Bacterial reverse mutation assay (AMES) ative
Genot	toxicity in vivo	Species: Ra Application Result: neg	Route: Intraperitoneal injection
	amidopropyl betaine: toxicity in vitro	Method: Of Result: neg	Bacterial reverse mutation assay (AMES) ECD Test Guideline 471 ative Based on data from similar materials
Genot	toxicity in vivo	cytogenetic Species: M Application Result: neg	ouse Route: Ingestion
	ium dioxide: toxicity in vitro	: Test Type: Result: neg	Bacterial reverse mutation assay (AMES) ative
Genot	toxicity in vivo	: Test Type: Species: M Result: neg	
	nogenicity assified based on availa	able information.	
Ingree Titani Specie Applic Expos Metho	dients: ium dioxide: es: Rat cation Route: inhalation sure time: 24 Months od: OECD Test Guidelir t: positive	(dust/mist/fume)	

Remarks: The mechanism or mode of action may not be relevant in humans. The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.



rsion	Revision Date: 03/03/2015	MSDS Number: 66483-00002	Date of last issue: 02/26/2015 Date of first issue: 02/26/2015		
Carcir ment	nogenicity - Assess-	: Limited evidence animals.	e of carcinogenicity in inhalation studies with		
IARC	:	Group 2B: Possibl	y carcinogenic to humans		
		Titanium dioxide	13463-67		
OSHA			No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.		
NTP			No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.		
-	oductive toxicity assified based on availa	ble information.			
Ingre	dients:				
Species: Rat Application Route: Ingestion Result: negative					
Effect	s on fetal development	ent : Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: negative			
<b>Cocoamidopropyl betaine:</b> Effects on fetal development		Species: Rat Application Rou Method: OECD Result: negative	Test Guideline 414		
	-single exposure assified based on availa	ble information.			
	-repeated exposure				
	assified based on availa	ble information.			
Repe	ated dose toxicity				
<b>Distil</b> Speci NOAE Applic	dients: lates (petroleum), hydi es: Rat EL: > 10.4 mg/l cation Route: inhalation sure time: 90 d	-			



Version	Revision Date:	MSDS Number:
1.1	03/03/2015	66483-00002

Date of last issue: 02/26/2015 Date of first issue: 02/26/2015

Remarks: Based on data from similar materials

#### Cocoamidopropyl betaine:

Species: Rat NOAEL: 250 mg/kg Application Route: Ingestion Exposure time: 90 d Method: OECD Test Guideline 408 Remarks: Based on data from similar materials

#### Titanium dioxide:

Species: Rat NOAEL: 24,000 mg/kg Application Route: Ingestion Exposure time: 28 d

Species: Rat NOAEL: 10 mg/m3 Application Route: inhalation (dust/mist/fume) Exposure time: 2 y Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

### Aspiration toxicity

Not classified based on available information.

### Product:

No aspiration toxicity classification

#### Ingredients:

#### Distillates (petroleum), hydrotreated light:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **SECTION 12. ECOLOGICAL INFORMATION**

## Ecotoxicity

Ingredients: Distillates (petroleum), hydrotreated light:				
Toxicity to fish	<ul> <li>LL50 (Danio rerio (zebra fish)): &gt; 250 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203</li> </ul>			
Toxicity to daphnia and other aquatic invertebrates	<ul> <li>EL50 (Acartia tonsa): &gt; 3,193 mg/l</li> <li>Exposure time: 48 h</li> <li>Test substance: Water Accommodated Fraction</li> </ul>			
Toxicity to algae	<ul> <li>EL50 (Skeletonema costatum (marine diatom)): &gt; 3,200 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction</li> </ul>			



/ersion .1	Revision Date: 03/03/2015		SDS Number: 483-00002	Date of last issue: 02/26/2015 Date of first issue: 02/26/2015
			Exposure time:	onema costatum (marine diatom)): 993 mg/l 72 h Water Accommodated Fraction
aquati	ty to daphnia and other c invertebrates nic toxicity)	:	Exposure time:	aphnia dubia (water flea)): > 70 mg/l 8 d Water Accommodated Fraction
Toxici	ty to bacteria	:	EC50: > 100 mg Exposure time:	
	<b>amidopropyl betaine:</b> ty to fish	:	LC50: > 1 - 10 r Exposure time: Method: ISO 73 Remarks: Base	96 h
Toxici	ty to bacteria	:		g/l Test Guideline 209 d on data from similar materials
	<b>um dioxide:</b> ty to fish	:	Exposure time:	nchus mykiss (rainbow trout)): > 100 mg/l 96 h Test Guideline 203
	ty to daphnia and other c invertebrates	:	EC50 (Daphnia Exposure time:	magna (Water flea)): > 100 mg/l 48 h
Toxici	ty to algae	:	EC50 (Skeleton Exposure time:	ema costatum (marine diatom)): > 10,000 mg, 72 h
Toxici	ty to bacteria	:	EC50: > 1,000 r Exposure time: Method: OECD	
	<b>oro-2-methyl-4-isothia</b> ty to fish		LC50 (Oncorhy Exposure time:	nchus mykiss (rainbow trout)): 0.19 mg/l 96 h d on data from similar materials
	ty to daphnia and other c invertebrates	:	Exposure time:	magna (Water flea)): 0.16 mg/l 48 h d on data from similar materials
Toxici	ty to algae	:	Exposure time:	rum capricornutum (green algae)): 0.027 mg/l 72 h d on data from similar materials
M-Fac icity)	ctor (Acute aquatic tox-	:	10	



Version 1.1	Revision Date: 03/03/2015	-	DS Number: 83-00002	Date of last issue: 02/26/2015 Date of first issue: 02/26/2015
Pers	sistence and degradabi	lity		
Ingr	edients:			
	<b>illates (petroleum), hyc</b> legradability		Result: Readily Biodegradation Exposure time:	
	<b>bhols, C10-16, ethoxyla</b> legradability			<b>n salts:</b> biodegradable.
	oamidopropyl betaine: legradability		Biodegradation Exposure time: Method: OECD	
	n <b>loro-2-methyl-4-isothi</b> a legradability			dily biodegradable.
Bioa	accumulative potential			
5-CI Part	edients: nloro-2-methyl-4-isothia ition coefficient: n- nol/water		<b>-3-one:</b> log Pow: 0.401	
Mob	oility in soil			
No c	lata available			
	<b>er adverse effects</b> data available			
SECTIO	SECTION 13. DISPOSAL CONSIDERATIONS			
Disp	oosal methods			
Was	te from residues	:	Dispose of in a	ccordance with local regulations.
Con	taminated packaging	:	Empty containe	inused product. ers should be taken to an approved waste r recycling or disposal.

### **SECTION 14. TRANSPORT INFORMATION**

### International Regulation

UNRTDG Not regulated as a dangerous good IATA-DGR



Version 1.1	Revision Date: 03/03/2015	MSDS Number: 66483-00002	Date of last issue: 02/26/2 Date of first issue: 02/26/2	
Not r	egulated as a dangero	us good		
	<b>3-Code</b> egulated as a dangero	us good		
	sport in bulk accordin applicable for product a	-	POL 73/78 and the IBC Cod	le
Dom	estic regulation			
<b>49 C</b> Not r	FR egulated as a dangero	us good		
SECTION	15. REGULATORY IN	FORMATION		
EPC	RA - Emergency Plan	ning and Community	Right-to-Know	
	CLA Reportable Quar material does not conta	<b>ntity</b> ain any components wit	h a CERCLA RQ.	
	-	ardous Substances Re ain any components wit	portable Quantity h a section 304 EHS RQ.	
SAR	A 311/312 Hazards	: Acute Health Ha	zard	
SAR	A 302		this material are subject to th SARA Title III, Section 302.	ne reporting
SAR	A 313	known CAS num	es not contain any chemical bers that exceed the thresho established by SARA Title III	old (De Minimis)
Penr	isylvania Right To Kn	low		
	Walnut see Alcohols, C	C10-16, ethoxylated, sul	84012-43-1	30 - 50 % 10 - 20 % 5 - 10 % 5 - 10 %
	sodium salts Castor oil, sulfated Titanium dioxide 2-Phenoxyethanol		8002-33-3 13463-67-7 122-99-6	5 - 10 % 1 - 5 % 0.1 - 1 %
New	Jersey Right To Know	w		
	Walnut see Alcohols, C	C10-16, ethoxylated, sul	84012-43-1	30 - 50 % 10 - 20 % 5 - 10 % 5 - 10 %
	sodium sal			F 40.0/

California Prop 65

Castor oil, sulfated

Titanium dioxide

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

8002-33-3

13463-67-7

5 - 10 %


1 - 5 %



1.1         03/03/2015         66483-00002         Date of first issue: 02/26/2015				ate of last issue: 02/26/2015 ate of first issue: 02/26/2015
--	--	--	--	---

#### **SECTION 16. OTHER INFORMATION**

#### Further information



#### HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

#### Full text of other abbreviations

ACGIH NIOSH REL OSHA Z-1	:	USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average
Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen- cy, http://echa.europa.eu/
Revision Date	:	03/03/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8