

# **Material Safety Data Sheet**

Issuing Date 21-Nov-2013

Revision Date 13-Jan-2015

**Revision Number 1** 

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Ru-Glyde

Product Code(s) RG-18, RG-18BK, RG-18CT, RG-18MY, RG-20, RG-20BK, RG-20MY, RG-55, RG-55BK,

**RGC-18, RGC-20** 

Recommended Use Tire Mounting and Rubber Lubricant

**Synonyms** Tire Mounting Lubricant.

Supplier Address

AGS Company P.O. Box 729 Muskegon, MI 49443

TEL: 800-253-0403

**Emergency Telephone** 

Number

800-255-3924

# 2. HAZARDS IDENTIFICATION

#### DANGER!

# **Emergency Overview**

Harmful if swallowed or if inhaled Irritating to eyes, respiratory system and skin Contains a known or suspected carcinogen Contains a known or suspected reproductive toxin

Appearance Tea colored Physical State Liquid. Odor Odorless

Potential Health Effects

Principle Routes of Exposure Inhalation. Skin contact. Eye contact.

**Acute Toxicity** 

Eyes Irritating to eyes.
Skin Irritating to skin.
Inhalation Harmful by inhalation.
Ingestion Harmful if swallowed.

Chronic Effects Chromium and chromium compounds are currently classified by IARC and National

Toxicology Program as known carcinogens.

Aggravated Medical Conditions Pre-existing eye disorders. Skin disorders. Respiratory disorders. Reproductive system.

Interactions with Other Chemicals Use of alcoholic beverages may enhance toxic effects.

**Environmental Hazard** See Section 12 for additional Ecological Information.

\_\_\_\_\_

Page 1/7

Note: Ru-Glyde has both GHS SDS and NA MSDS formats

Page 30

WPS-AGS-005 - Ru-Glyde

Revision Date 13-Jan-2015

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Potassium hydroxide	1310-58-3	7.08
Sodium dichromate, dihydrate	7789-12-0	6.93
Ethylene glycol	107-21-1	2.28
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	0.16

#### 4. FIRST AID MEASURES

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Call a physician immediately.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Remove and wash

contaminated clothing before re-use. Get medical attention immediately if symptoms occur.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately if

symptoms occur.

**Ingestion** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink

plenty of water. Call a physician or Poison Control Center immediately.

Notes to Physician Treat symptomatically.

**Protection of First-aiders**Use personal protective equipment. Avoid contact with skin, eyes and clothing.

#### 5. FIRE-FIGHTING MEASURES

Flammable Properties Not flammable.

Flash Point Not determined.

surrounding environment.

**Explosion Data** 

Sensitivity to Mechanical Impact
Sensitivity to Static Discharge

None. None

Specific Hazards Arising from the Chemical

Containers may explode when heated.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear.

NFPA Health Hazard 2 Flammability 0 Instability 0 Physical and Chemical

Hazards -

HMIS Health Hazard 2\* Flammability 0 Physical Hazard 0 Personal Protection X

\*Indicates a chronic health hazard.

## 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use

personal protective equipment. Avoid contact with skin, eyes and clothing. Avoid breathing

vapors or mists.

Environmental Precautions Do not allow material to contaminate ground water system. Prevent product from entering

drains.

Page 30 Revision Date 13-Jan-2015 WPS-AGS-005 - Ru-Glyde

**Methods for Containment** Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later

disposal.

**Methods for Cleaning Up** Dam up. Soak up with inert absorbent material. Use personal protective equipment. Sweep

up and shovel into suitable containers for disposal.

Other Information Refer to protective measures listed in Sections 7 and 8.

#### 7. HANDLING AND STORAGE

Handling Ensure adequate ventilation. Wear personal protective equipment. Avoid contact with skin,

eyes and clothing. Avoid breathing vapors or mists. Wash thoroughly after handling.

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly

labeled containers.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Sodium dichromate, dihydrate	TWA: 0.05 mg/m <sup>3</sup> Cr	(vacated) Ceiling: 0.1 mg/m <sup>3</sup>	IDLH: 15 mg/m <sup>3</sup> Cr(VI)
7789-12-0		Ceiling: 0.1 mg/m³ CrO3 applies	TWA: 0.001 mg/m <sup>3</sup> Cr
		to any operations or sectors for	
		which the Hexavalent Chromium	
		standard [29 CFR 1910.1026] is	
		stayed or is otherwise not in	
		effect	
Ethylene glycol	Ceiling: 100 mg/m³ aerosol only	(vacated) Ceiling: 50 ppm	-
107-21-1		(vacated) Ceiling: 125 mg/m <sup>3</sup>	

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. NIOSH IDLH: Immediately Dangerous to Life or Health.

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Engineering Measures** Showers

Eyewash stations Ventilation systems

Personal Protective Equipment

**Eve/Face Protection Skin and Body Protection**  Tightly fitting safety goggles. Face-shield.

Wear protective gloves/clothing.

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved **Respiratory Protection** 

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

**Hygiene Measures** When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area

and clothing.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Odorless. Tea colored. Odor **Appearance** No information available. Liquid **Odor Threshold Physical State** 

pН

No information available.

**Autoignition Temperature Boiling Point/Boiling Range**  No information available.

**Flash Point Decomposition Temperature** Melting Point/Range

No information available. No information available.

Flammability Limits in Air

100 °C / 212 °F

No information available.

**Specific Gravity** 1.01 Water Solubility Completely soluble

Page 30

WPS-AGS-005 - Ru-Glyde Revision Date 13-Jan-2015

Solubility No information available. Evaporation available. Vapor Pressure No data available. Vapor De

**Evaporation Rate** Slower than Butyl Acetate **Vapor Density** Heavier than air @ Air = 1

10. STABILITY AND REACTIVITY

**Stability** Stable under recommended storage conditions.

2.3199999704957

Incompatible Products Incompatible with oxidizing agents. Hydrazine Acids. Halogenated compounds.

**Conditions to Avoid** Exposure to air or moisture over prolonged periods.

Hazardous Decomposition Products Sodium oxides. Potassium oxides.

**Hazardous Polymerization** Hazardous polymerization does not occur.

## 11. TOXICOLOGICAL INFORMATION

**Acute Toxicity** 

**VOC Content (%)** 

**Product Information** 

**Inhalation** Harmful by inhalation.

Eye Contact Irritating to eyes.

**Skin Contact** Irritating to skin.

**Ingestion** Harmful if swallowed.

**Chronic Toxicity** 

Chronic Toxicity Chromium and chromium compounds are currently classified by IARC and National

Toxicology Program as known carcinogens.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Petroleum products are known to cause cancer because of carcinogenic components (e.g. benzene, DMSO). These carcinogenic components are typically found in crude petroleum

products and are removed through the refinement process.

Chemical Name	ACGIH	IARC	NTP	OSHA
Sodium dichromate, dihydrate	A1	Group 1	Known	
Petroleum distillates, solvent dewaxed heavy paraffinic	A2	Group 1		X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans
NTP: (National Toxicity Program)
Known - Known Carcinogen

**OSHA: (Occupational Safety & Health Administration)** 

X - Present

Target Organ Effects Eyes. Respiratory system. Skin. Bladder.

#### 12. ECOLOGICAL INFORMATION

**Ecotoxicity** 

The environmental impact of this product has not been fully investigated.

Domo A17

WPS-AGS-005 - Ru-Glyde Revision Date 13-Jan-2015

Chemical Name	Toxicity to Algae	Toxicity	to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Ethylene glycol	EC50 96 h: 6500 - 13000 mg/L (Pseudokirchneriella subcapitata)			EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620.0 mg/L 30 min	EC50 48 h: = 46300 mg/L (Daphnia magna)
Petroleum distillates, solvent dewaxed heavy paraffinic		LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss)			EC50 48 h: > 1000 mg/L (Daphnia magna)
(	Chemical Name		Log Pow	, , , , ,	
Potassium hydroxide		0.83			
	Ethylene glycol			-1.93	

# 13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

**Contaminated Packaging** Do not re-use empty containers.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste	
Potassium hydroxide	Toxic	
	Corrosive	
Sodium dichromate, dihydrate	Toxic	
•	Corrosive	
	Ignitable	

# 14. TRANSPORT INFORMATION

**DOT** Not regulated

TDG Not regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

TSCA Complies DSL Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

Page 5/7

WPS-AGS-005 - Ru-Glyde Revision Date 13-Jan-2015

#### U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Ethylene glycol	107-21-1	2.28	1.0

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### **Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Potassium hydroxide	1000 lb			X
Sodium dichromate, dihydrate		Х		

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Potassium hydroxide	1000 lb		RQ 1000 lb final RQ
			RQ 454 kg final RQ
Ethylene glycol	5000 lb		RQ 5000 lb final RQ
			RQ 2270 kg final RQ

## **U.S. State Regulations**

# California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Sodium dichromate, dihydrate	7789-12-0	Carcinogen
		Developmental

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Sodium dichromate, dihydrate			Х	Х	Х
Ethylene glycol	X	Х	Х	X	X

International Regulations

intornational regulations		
Chemical Name	Carcinogen Status	Exposure Limits
Sodium dichromate, dihydrate	A1	Mexico: TWA 0.05 mg/m <sup>3</sup>
		Mexico: TWA 0.5 mg/m <sup>3</sup>
Ethylene glycol		Mexico: Ceiling 100 mg/m <sup>3</sup>

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

Page 30

WPS-AGS-005 - Ru-Glyde

Revision Date 13-Jan-2015

WUMIS Hazard Class

WHMIS Hazard Class
D2A Very toxic materials
D2B Toxic materials



Canadian National Pollutant Release Inventory (NPRI)

Component	NPRI
Sodium dichromate, dihydrate 7789-12-0 ( 6.93 )	X
Ethylene glycol 107-21-1 ( 2.28 )	X

Legend X - Listed

## **16. OTHER INFORMATION**

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110

1-800-572-6501 21-Nov-2013

Issuing Date21-Nov-2013Revision Date13-Jan-2015Revision NoteNew regional format

General Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**