# malku

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Power Brite

Other means of identification

Product Code 1060

Recommended use Wheel Cleaner Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Malco Products, Inc.

Address 361 Fairview Ave
Barberton, OH 44203

**United States** 

Telephone Phone 800-253-2526

Fax 330-753-2025

Website www.malcopro.com
E-mail msdsinfo@malcopro.com
Contact person Technical Department

Emergency phone number Phone 1-800-424-9300

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 3

Acute toxicity, dermal

Acute toxicity, inhalation

Skin corrosion/irritation

Serious eye damage/eye irritation

Category 1

Specific target organ toxicity, repeated

Category 1

Category 1

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Toxic if swallowed. Fatal in contact with skin. Causes severe skin burns and eye damage. Causes

serious eye damage. Harmful if inhaled.

**Precautionary statement** 

Prevention Keep away from flames and hot surfaces-No smoking. Do not breathe mist or vapor. Do not get in

eyes, on skin, or on clothing. Wash thoroughly after handling. Do not eat, drink or smoke when

using this product. Use only outdoors or in a well-ventilated area. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. If swallowed: Rinse mouth. Do NOT induce

vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Immediately call a poison center/doctor. Take off immediately all contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to

extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Supplemental information

classified (HNOC)

Hazard(s) not otherwise

Dispose of contents/container in accordance with local/regional/national/international regulations.

None known.

% of the mixture consists of component(s) of unknown acute oral toxicity. 3.88% of the mixture consists of component(s) of unknown acute dermal toxicity.

# 3. Composition/information on ingredients

#### **Mixtures**

Ingestion

Chemical name	Common name and synonyms	CAS number	<u></u> %
Hydrogen Fluoride		7664-39-3	5 - < 10
Ethylene Glycol Monobutyle	ther	111-76-2	3 - < 5
Other components below re	portable levels		90 - 100

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or Skin contact poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

> Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use

> > mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of

a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**General information** 

Take off immediately all contaminated clothing. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Discard any shoes or clothing items that cannot be decontaminated.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Specific methods

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Should not be released into the environment.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

#### **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

# Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910,1000)

#### Occupational exposure limits

Components	Туре	Value	
Ethylene Glycol Monobutylether (CAS 111-76-2)	PEL	240 mg/m3	
•		50 ppm	
US. OSHA Table Z-2 (29 CFR 191	0.1000)		
Components	Туре	Value	
Hydrogen Fluoride (CAS 7664-39-3)	TWA	3 ppm	
<b>US. ACGIH Threshold Limit Value</b>	es		
Components	Туре	Value	
Ethylene Glycol Monobutylether (CAS 111-76-2)	TWA	20 ppm	
Hydrogen Fluoride (CAS 7664-39-3)	Ceiling	2 ppm	
,	TWA	0.5 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Type	Value	
Ethylene Glycol Monobutylether (CAS 111-76-2)	TWA	24 mg/m3	
,		5 ppm	
Hydrogen Fluoride (CAS 7664-39-3)	Ceiling	5 mg/m3	
,		6 ppm	
	TWA	2.5 mg/m3	
		3 ppm	

#### **Biological limit values**

#### **ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Ethylene Glycol Monobutylether (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

# US - California OELs: Skin designation

Ethylene Glycol Monobutylether (CAS 111-76-2) Can be absorbed through the skin. Hydrogen Fluoride (CAS 7664-39-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Ethylene Glycol Monobutylether (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Ethylene Glycol Monobutylether (CAS 111-76-2) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

Hydrogen Fluoride (CAS 7664-39-3) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Ethylene Glycol Monobutylether (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Ethylene Glycol Monobutylether (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

#### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove **Hand protection** 

supplier.

Wear appropriate chemical resistant clothing. Other

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** Clear. Physical state Liquid. **Form** Liquid. Color Amber Butyl Odor

**Odor threshold** Not available.

Not available. Melting point/freezing point Not available. Initial boiling point and boiling

range

Flash point Not available. Not available. **Evaporation rate** Flammability (solid, gas) Not applicable.

Material name: Power Brite 4 / 10

1060 Version #: 02 Revision date: 04-27-2016 Issue date: 05-06-2015

# Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure
Not available.
Vapor density
Not available.
Relative density
Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density8.40 lbs/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.

Specific gravity 1.01

VOC (Weight %) 2.5 % w/w by weight

# 10. Stability and reactivity

Reactivity Reacts violently with strong alkaline substances. This product may react with reducing agents.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

Hazardous polymerization does not occur.

reactions

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Do not mix with other chemicals. Contact with incompatible materials.

Incompatible materials Bases. Reducing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation Harmful if inhaled.

**Skin contact** Fatal in contact with skin. Causes severe skin burns.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

**Eye contact** Causes serious eye damage.

**Ingestion** Toxic if swallowed. Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Information on toxicological effects

Acute toxicity Fatal in contact with skin. Toxic if swallowed. Harmful if inhaled.

Components Species Test Results

Ethylene Glycol Monobutylether (CAS 111-76-2)

**Acute** 

**Dermal** 

LD50 Rabbit 400 mg/kg

Inhalation

LC50 Mouse 700 ppm, 7 Hours

Rat 450 ppm, 4 Hours

Oral

LD50 Guinea pig 1.2 g/kg

 Mouse
 1.2 g/kg

 Rabbit
 0.32 g/kg

 Rat
 560 mg/kg

Hydrogen Fluoride (CAS 7664-39-3)

Acute Inhalation

LC50 Guinea pig 4327 ppm, 15 Minutes

3.54 mg/l, 15 Minutes

Mouse 500 ppm, 1 Hours
Rat 4970 ppm, 5 Minutes

2689 ppm, 15 Minutes 2042 ppm, 30 Minutes 1278 ppm, 1 Hours

**Skin corrosion/irritation** Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylene Glycol Monobutylether (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

Chronic effects May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

# 12. Ecological information

**Ecotoxicity** 

Because of the low pH of this product, it would be expected to produce significant ecotoxicity upon

exposure to aquatic organisms and aquatic systems.

Components Species **Test Results** 

Ethylene Glycol Monobutylether (CAS 111-76-2)

**Aquatic** 

Fish LC50 Inland silverside (Menidia beryllina) 1250 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethylene Glycol Monobutylether 0.83

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow **Disposal instructions** 

this material to drain into sewers/water supplies. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

**UN** number UN3264

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrofluoric Acid) UN proper shipping name

Transport hazard class(es)

Class 8 Subsidiary risk 8 Label(s) Ш Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B2. IB2. T11. TP2. TP27

Packaging exceptions None 202 Packaging non bulk Packaging bulk 243

IATA

**UN** number UN3264

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrofluoric Acid) **UN proper shipping name** 

Transport hazard class(es)

Class 8 Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 81

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed.

Material name: Power Brite SDS US

1060 Version #: 02 Revision date: 04-27-2016 Issue date: 05-06-2015

Cargo aircraft only Allowed.

**IMDG** 

UN number UN3264

UN proper shipping name CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrofluoric Acid)

Transport hazard class(es)

Class 8
Subsidiary risk Packing group || Environmental hazards

Marine pollutant No. nS F-A, S-B

EmS F-A, S-B
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

DOT



IATA; IMDG



# 15. Regulatory information

**US federal regulations**This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Hydrogen Fluoride (CAS 7664-39-3) Listed.

SARA 304 Emergency release notification

Hydrogen Fluoride (CAS 7664-39-3) 100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value	
Hydrogen Fluoride	7664-39-3	100	100 lbs			

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Hydrogen Fluoride	7664-39-3	5 - < 10	

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Nο

Hydrogen Fluoride (CAS 7664-39-3)

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Hydrogen Fluoride (CAS 7664-39-3) **Safe Drinking Water Act**Not regulated.

(SDWA)

# **US state regulations**

# US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Ethylene Glycol Monobutylether (CAS 111-76-2)

Hydrogen Fluoride (CAS 7664-39-3)

#### **US. Massachusetts RTK - Substance List**

Ethylene Glycol Monobutylether (CAS 111-76-2)

Hydrogen Fluoride (CAS 7664-39-3)

# US. New Jersey Worker and Community Right-to-Know Act

Ethylene Glycol Monobutylether (CAS 111-76-2)

Hydrogen Fluoride (CAS 7664-39-3)

# US. Pennsylvania Worker and Community Right-to-Know Law

Ethylene Glycol Monobutylether (CAS 111-76-2)

Hydrogen Fluoride (CAS 7664-39-3)

## **US. Rhode Island RTK**

Hydrogen Fluoride (CAS 7664-39-3)

# **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

# International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date 05-06-2015 04-27-2016 **Revision date** 

Version # 02

Malco Automotive cannot anticipate all conditions under which this information and its product, or Disclaimer

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless

specified in the text.

Hazard(s) identification: Hazard statement **Revision Information** 

Hazard(s) identification: Prevention Hazard(s) identification: Response

Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Multiple Properties Transport Information: Material Transportation Information

GHS: Classification

Material name: Power Brite SDS US 10 / 10 1060 Version #: 02 Revision date: 04-27-2016 Issue date: 05-06-2015