# malku

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Prizm Dressing

Other means of identification

Product Code 1235
Recommended use Dressing
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Malco Products, Inc.
Address 361 Fairview Ave
Barberton, OH 44203

**United States** 

Telephone Phone 800-253-2526

Fax 330-753-2025

Website www.malcopro.com
E-mail msdsinfo@malcopro.com
Contact person Technical Department

Emergency phone number Phone 1-800-424-9300

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsAcute toxicity, oralCategory 5

Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements





Signal word Danger

Hazard statement Highly flammable liquid and vapor. May be harmful if swallowed. May be fatal if swallowed and

enters airways.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting. In case

of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Solvent Naphtha (Petroleum), Light Aliph.		64742-89-8	80 - < 90
Siloxanes And Silicones, Di-me		63148-62-9	20 - < 30
Other components below reportable le	evels		< 0.1

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

temporary irritation.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists.

Eve contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

**General information** 

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Specific hazards arising from the chemical

Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor.

# 6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

#### **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

# 7. Handling and storage

#### Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid spark promoters. Eliminate sources of ignition. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Refrigeration recommended. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

Occupational exposure limits

No exposure limits noted for ingredient(s).

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

Explosion-proof general and local exhaust ventilation.

controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other

Wear suitable protective clothing.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### 9. Physical and chemical properties

**Appearance** 

Clear.

Material name: Prizm Dressing sps us

**Physical state** Liquid. Liquid. **Form** Color Blue Solvent. Odor **Odor threshold** Not available.

none

Melting point/freezing point Not available.

Initial boiling point and boiling

range

246 °F (118.89 °C) estimated

44.0 °F (6.7 °C) estimated Flash point

Not available. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits Flammability limit - lower Not available.

(%)

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%) Not available. Vapor pressure Vapor density Not available. Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Density** 6.70 lb/gal

Flammable IB estimated Flammability class

VOC (Weight %) 80 % by weight

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

#### Information on likely routes of exposure

No adverse effects due to inhalation are expected. Inhalation Skin contact No adverse effects due to skin contact are expected. Direct contact with eyes may cause temporary irritation. Eye contact

May be harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or Ingestion

vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** May be fatal if swallowed and enters airways.

#### 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results** 

Siloxanes And Silicones, Di-me (CAS 63148-62-9)

Aquatic

Fish LC50 Channel catfish (Ictalurus punctatus) 2.36 - 4.15 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions** 

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

# 14. Transport information

DOT

UN1993 **UN number** 

Flammable liquids, n.o.s. UN proper shipping name

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Transport hazard class(es)

3 Class Subsidiary risk 3 Label(s) Packing group Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**Special provisions** IB2, T7, TP1, TP8, TP28

Packaging exceptions 150 Packaging non bulk 202 Packaging bulk 242

**IATA** 

**UN** number UN1993

**UN** proper shipping name Flammable liquid, n.o.s.

Transport hazard class(es)

3 Class Subsidiary risk Packing group Ш **Environmental hazards** No. **ERG Code** 3H

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only Allowed.

**IMDG** 

UN1993 **UN** number

FLAMMABLE LIQUID, N.O.S. **UN proper shipping name** 

Transport hazard class(es)

Not available.

3 **Class** Subsidiary risk П Packing group

**Environmental hazards** 

Marine pollutant No. **EmS** F-E, S-E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



## 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

#### SARA 313 (TRI reporting)

Not regulated.

# Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **US** state regulations

# US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Solvent Naphtha (Petroleum), Light Aliph. (CAS 64742-89-8)

#### **US. Massachusetts RTK - Substance List**

Not regulated.

#### US. New Jersey Worker and Community Right-to-Know Act

Not listed.

#### US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

#### US. Rhode Island RTK

Not regulated.

#### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Material name: Prizm Dressing sps us

Country(s) or regionInventory nameOn inventory (yes/no)\*EuropeEuropean Inventory of Existing Commercial ChemicalNo

Substances (EINECS)

EuropeEuropean List of Notified Chemical Substances (ELINCS)NoJapanInventory of Existing and New Chemical Substances (ENCS)NoKoreaExisting Chemicals List (ECL)YesNew ZealandNew Zealand InventoryYesPhilippinesPhilippine Inventory of Chemicals and Chemical SubstancesYes

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

# 16. Other information, including date of preparation or last revision

 Issue date
 11-02-2014

 Revision date
 03-24-2015

Version # 02

**Disclaimer** Malco Automotive cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless

specified in the text.

**Revision Information** Hazard(s) identification: Hazard statement

Hazard(s) identification: Prevention Hazard(s) identification: Response

Handling and storage: Precautions for safe handling Exposure controls/personal protection: Eye/face protection Exposure controls/personal protection: Respiratory protection

Exposure controls/personal protection: Other

Exposure controls/personal protection: PPE Symbols Physical & Chemical Properties: Multiple Properties

Toxicological information: Carcinogenicity Toxicological information: Mutagenicity

Regulatory Information: Risk Phrases - Labeling

Material name: Prizm Dressing sps us

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).