# malku

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Prizm Turbo Shine

Other means of identification

Product Code 1965
Recommended use Dressing
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Malco Products, Inc.

Address 361 Fairview Ave
Barberton, OH 44203

**United States** 

**Telephone** Phone 800-253-2526

Fax 330-753-2025

Website www.malcopro.com
E-mail msdsinfo@malcopro.com
Contact person Technical Department

Emergency phone number Phone 1-800-424-9300

# 2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsAcute toxicity, oralCategory 5Serious eye damage/eye irritationCategory 2Germ cell mutagenicityCategory 1BCarcinogenicityCategory 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. May be harmful if swallowed. May be fatal if swallowed and

enters airways. Causes serious eye irritation. May cause drowsiness or dizziness. May cause

genetic defects. May cause cancer.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection. Wear protective gloves/protective clothing/eye protection/face protection.

Material name: Prizm Turbo Shine SDS US

If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all Response

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to

extinguish.

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Storage

Keep cool. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal** 

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name Common name and synon		CAS number	<u></u> %	
NAPHTHA (PETROLEUM), LIGHT ALKYLATE		64741-66-8	40 - < 50	
IPA		67-63-0	30 - < 40	
Siloxanes And Silicones, Di-me		63148-62-9	20 - < 30	
Other components below reportable lev	els		< 1	

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

**General information** 

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth Suitable extinguishing media

may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Specific methods General fire hazards In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

# 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)			
Components	Туре	Value	
IPA (CAS 67-63-0)	PEL	980 mg/m3 400 ppm	

Material name: Prizm Turbo Shine 1965 Version #: 01 Issue date: 05-12-2015

Components	Туре	Value	
IPA (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
US. NIOSH: Pocket Guide to C	Chemical Hazards		
Components	Туре	Value	
IPA (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	500 ppm 980 mg/m3	

#### **Biological limit values**

<b>ACGIH</b>	Biological	<b>Exposure</b>	Indices
--------------	------------	-----------------	---------

Components	Value	Determinant	Specimen	Sampling Time
IPA (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

# Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

**Respiratory protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

Appearance Clear.
Physical state Liquid.
Form Liquid.
Color Blue
Odor Cherry
Odor threshold Not available.
pH Not available.

Melting point/freezing point -127.3 °F (-88.5 °C) estimated Initial boiling point and boiling 180.5 °F (82.5 °C) estimated

range

Flash point 45.0 °F (7.2 °C)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

2.5 % estimated

Flammability limit - upper

(%)

12 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

60.53 hPa estimated Vapor pressure

Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water)

**Auto-ignition temperature** 750.2 °F (399 °C) estimated

**Decomposition temperature** Not available.

5 cP **Viscosity** 

68 °F (20 °C) Viscosity temperature

Other information

Density 6.55 lbs/gal **Explosive properties** Not explosive.

Flammability class Flammable IB estimated

6.4 cSt Kinematic viscosity Kinematic viscosity

temperature

68 °F (20 °C)

Not oxidizing. Oxidizing properties

VOC (Weight %) 79.5 % w/w by weight

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Isocyanates. Chlorine. Hazardous decomposition

products

No hazardous decomposition products are known.

#### 11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

May be harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or Ingestion

vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Headache. May cause drowsiness and dizziness. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging,

tearing, redness, swelling, and blurred vision.

#### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects.

Species	Test Results	
Rabbit	12800 mg/kg	
Dog	4797 mg/kg	
Mouse	3600 mg/kg	
	Rabbit Dog	Rabbit 12800 mg/kg Dog 4797 mg/kg

ComponentsSpeciesTest ResultsRabbit5.03 g/kgRat4.7 g/kg

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful.

# 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

IPA (CAS 67-63-0)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours

Siloxanes And Silicones, Di-me (CAS 63148-62-9)

Aquatic

Fish LC50 Channel catfish (Ictalurus punctatus) 2.36 - 4.15 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

IPA 0.05

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

# 14. Transport information

DOT

UN1993 **UN** number

**UN** proper shipping name Flammable liquids, n.o.s. (IPA and Petroleum Distillates)

Transport hazard class(es)

Class 3 Subsidiary risk 3 Label(s) П Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. **Special provisions** 

IB2, T7, TP1, TP8, TP28

150 Packaging exceptions Packaging non bulk 202 Packaging bulk 242

**IATA** 

UN1993 **UN** number

**UN** proper shipping name Flammable liquid, n.o.s. (IPA and Petroleum Distillates)

Transport hazard class(es)

Class 3 Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 3H

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo Allowed.

aircraft

Cargo aircraft only Allowed.

**IMDG** 

**UN** number UN1993

**UN** proper shipping name FLAMMABLE LIQUID, N.O.S. (IPA and Petroleum Distillates)

Not established.

Transport hazard class(es)

Class 3 Subsidiary risk **Packing group** Ш **Environmental hazards** 

Marine pollutant No. **EmS** F-E, S-E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



#### IATA; IMDG



# 15. Regulatory information

**US** federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

# Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **US** state regulations

# US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

#### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

IPA (CAS 67-63-0)

NAPHTHA (PETROLEUM), LIGHT ALKYLATE (CAS 64741-66-8)

**US. Massachusetts RTK - Substance List** 

IPA (CAS 67-63-0)

#### **US. New Jersey Worker and Community Right-to-Know Act**

IPA (CAS 67-63-0)

## US. Pennsylvania Worker and Community Right-to-Know Law

IPA (CAS 67-63-0)

#### **US. Rhode Island RTK**

IPA (CAS 67-63-0)

1965 Version #: 01 Issue date: 05-12-2015

# **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date 05-12-2015

Version #

Disclaimer

Malco Automotive cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

1965 Version #: 01 Issue date: 05-12-2015