

PART# A144G

Material Safety Data Sheet A144 White Sidewall Cleaner™



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: White Sidewall Cleaner™
Product Code: A144
Version Date: 09/07/10
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. COMPOSITION / INFORMATION ON INGREDIENTS

| COMPONENT | CAS # | ACGIH TLV | Exposure Limits | |
|---------------------|-----------|-----------------|-----------------|-----------------|
| | | | OSHA PEL | OTHER |
| Water | 7732-18-5 | Not established | Not established | Not established |
| Glycol ether | 111-76-2 | 20 ppm [skin] | 50 ppm [skin] | Not established |
| Nonionic surfactant | 9016-45-9 | Not established | Not established | Not established |
| Surfactant | 9004-87-9 | Not established | Not established | Not established |

3. HAZARDS IDENTIFICATION

POTENTIAL ACUTE [single or short term] HEALTH EFFECTS OF OVEREXPOSURE

Eye : May cause eye irritation. Symptoms may include stinging, tearing, and redness.

Skin : Skin contact may cause irritation. Symptoms may include redness, discomfort, drying and cracking, or rash. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion : Swallowing small amounts during handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.

Inhalation : Breathing large amounts may be harmful. Symptoms are more typically seen at air concentrations exceeding the recommended exposure limits. Symptoms of exposure may include: initial Central Nervous System excitation (euphoria, exhilaration, light-headedness) followed by CNS depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other CNS effects, such as confusion, impaired coordination, coma, and death. Breathing small amounts during handling is not likely to cause harmful effects.

POTENTIAL CHRONIC [long term] HEALTH EFFECTS OF OVEREXPOSURE:

General Effects: This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain. Acute lethal exposures in animal studies of a product component has resulted in congestion of organs including kidney, spleen and lungs. mild, reversible kidney effects. mild, reversible liver effects. blood abnormalities. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: Skin sensitization.

Cancer Information: THIS PRODUCT CONTAINS NO COMPONENTS LISTED AS CARCINOGENIC BY IARC, NTP, OR OSHA 1910(Z)

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

By nature of the product, no adverse health effects are expected. However, all industrial chemicals should be handled with caution to avoid unnecessary exposure.

HMS® III* HAZARDOUS WARNINGS:

Health: 2 Flammability: 2 Physical: 0 Personal Protective Equipment: See Section 8

* See www.paint.org/hmis or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.

Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Seek medical attention if symptoms persist. Wash clothing before reuse.

Ingestion: Do not induce vomiting. Aspiration into the lungs can cause serious damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Contact a physician, medical facility, or poison control center immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep the victim warm and quiet. Seek immediate medical attention.

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: lung (for example, asthma-like conditions); liver; kidney; skin;

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: Product is water based material, containing minor amounts of combustible ingredients. "Empty" containers retain product residue and can be dangerous.

Fire Fighting Instructions: Use water spray, foam, dry chemical, or CO2. Do not direct a solid stream of water or foam into hot burning pools, this may cause frothing and increase fire intensity.

Flash Point: None°F PMCC None°C PMCC

Lower Flammability Limit: No data available

Upper Flammability Limit: No data available

Autoignition Temperature: No data available

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling: If ventilation is not sufficient, wear proper respiratory equipment. Avoid prolonged or repeated contact with skin. Do not use near ignition sources. Avoid prolonged or repeated breathing of vapor. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Avoid prolonged or repeated contact with skin.
Storage: Keep container tightly closed when not in use. Store in a cool, dry, well ventilated area away from all sources of ignition. Normal precautions common to safe manufacturing practice should be followed in handling and storage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated in "Section 2" of this MSDS (from known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be exceeded. No exposure limits exist for the constituents of this product.
Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available.
Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Respiratory Protection: No respiratory protection required under normal conditions of use. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|-------------------|--------------------|----------------------|------------------------------|
| Physical State: | Bulk liquid | Vapor Density: | [air = 1] 1.09 |
| Appearance: | Hazy | Evaporation Rate: | <0.020 (n-Butyl acetate = 1) |
| Odor: | None to very faint | Solubility in Water: | Complete; 100% |
| Specific Gravity: | 1.00 (H2O=1) | Boiling Point: | 212°F |
| Vapor Pressure: | .36 PSIG @ 70°F | pH: | 12-13.5 |

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.
Conditions to Avoid: Avoid contact with: Strong alkalis. Strong oxidizing agents. Reducing agents.
Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide.

11. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

12. TRANSPORTATION INFORMATION

| Agency | Proper Shipping name | UN Number | Hazard Class | Packing Group |
|--------|-------------------------|-----------|--------------|---------------|
| DOT | Not regulated by agency | | | |
| IATA | Not regulated by agency | | | |

13. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

| COMPONENT | CAS # | % BY WEIGHT | Regulatory Body |
|---------------------------------------|-------|-------------|------------------|
| No components listed in this section. | | | SARA Section 313 |

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.
No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.
No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.