

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Bead Sealer
- **Article number:** 14-101, 14-101A, 14-101B, 14-104, 14-104A, 14-104B
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture:** Sealant
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
31 Incorporated
100 Enterprise Dr.
Newcomerstown, OH 43832
Phone: (740) 498-8324
- **1.4 Emergency telephone number:**
ChemTel Inc.
+1 (800)255-3924, +1 (813)248-0585

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361d, H400, H410.
The following classifications are applicable only to OSHA (USA) regulations and not the specific CLP regulation: H361.



Repr. 2 H361: Suspected of damaging fertility or the unborn child.



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Repr. 2 H361d Suspected of damaging the unborn child. Route of exposure: Inhalation.
STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.



environment

Aquatic Acute 1 H400 Very toxic to aquatic life.
Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

(Cont'd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: **Bead Sealer**

(Cont'd. from page 1)



Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H336 May cause drowsiness or dizziness.

· **Additional information:**

0 % of the mixture consists of component(s) of unknown toxicity.
 There are no other hazards not otherwise classified that have been identified.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The substance is classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**

The following pictogram(s) are only for use within Europe: GHS09.



GHS02 GHS07 GHS08 GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

toluene
 natural rubber latex
 heptane

· **Hazard statements**

The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H361.

H361: Suspected of damaging fertility or the unborn child.

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361d, H410.

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child. Route of exposure: Inhalation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

H410 Very toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Cont'd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: **Bead Sealer**

(Cont'd. from page 2)

- P260 Do not breathe mist/vapours/spray.
 P264 Wash thoroughly after handling.
 P280 Wear protective gloves / eye protection / face protection.
 P233 Keep container tightly closed.
 P243 Take precautionary measures against static discharge.
 P271 Use only outdoors or in a well-ventilated area.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P314 Get medical advice/attention if you feel unwell.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



* - Indicates a long term health hazard from repeated or prolonged exposures.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 108-88-3	toluene	50-100%
EINECS: 203-625-9	Flam. Liq. 2, H225	
Index number: 601-021-00-3	Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304	
	Skin Irrit. 2, H315; STOT SE 3, H336	

(Cont'd. on page 4)

Safety Data Sheet






according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: **Bead Sealer**

(Cont'd. from page 3)

CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2	heptane  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Acute 1, H400; Aquatic Chronic 1, H410  Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 9006-04-6 EINECS: 232-689-0	natural rubber latex  Skin Sens. 1B, H317	<10%

• **Additional information:**

For the wording of the listed Hazard Statements refer to section 16.

For the listed ingredient(s), the identity and exact percentages are being withheld as a trade secret.

SECTION 4: First aid measures

• **4.1 Description of first aid measures**

• **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

• **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

• **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation is experienced, consult a doctor.

• **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:**

Rinse out mouth and then drink plenty of water.

A person vomiting while laying on their back should be turned onto their side.

Do not induce vomiting; call for medical help immediately.

• **4.2 Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Coughing

Cramp

Nausea

Allergic reactions

Gastric or intestinal disorders when ingested.

Disorientation

• **Hazards**

Danger of convulsion.

Danger of impaired breathing.

Danger of disturbed cardiac rhythm.

(Cont'd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: Bead Sealer

(Cont'd. from page 4)

Condition may deteriorate with alcohol consumption.

May be harmful in contact with skin.

May be harmful if inhaled.

Repeated exposure may cause skin dryness or cracking.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If necessary oxygen respiration treatment.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

Foam

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

Gaseous extinguishing agents

Water haze or fog

· **For safety reasons unsuitable extinguishing agents:** Water

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information** Eliminate all ignition sources if safe to do so.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

· **6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· **6.3 Methods and material for containment and cleaning up:**

Allow to solidify. Pick up mechanically.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Do not flush with water or aqueous cleansing agents

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Cont'd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: **Bead Sealer**

See Section 13 for disposal information.

(Cont'd. from page 5)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Flammable gas-air mixtures may form in empty receptacles.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.
 - Provide ventilation for receptacles.
 - Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
 - Store away from foodstuffs.
 - Store away from oxidising agents.
- **Further information about storage conditions:**
 - Store in cool, dry conditions in well sealed receptacles.
 - Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

PEL (USA)	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 75 mg/m ³ , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm R
EV (Canada)	Long-term value: 20 ppm

142-82-5 heptane

IOELV (EU)	Long-term value: 2085 mg/m ³ , 500 ppm
------------	---

(Cont'd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: Bead Sealer

(Cont'd. from page 6)

PEL (USA)	Long-term value: 2000 mg/m ³ , 500 ppm
REL (USA)	Short-term value: C 1800* mg/m ³ , C 440* ppm Long-term value: 350 mg/m ³ , 85 ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m ³ , 500 ppm Long-term value: 1640 mg/m ³ , 400 ppm
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2,045 mg/m ³ , 500 ppm Long-term value: 1,635 mg/m ³ , 400 ppm

9006-04-6 natural rubber latex	
---------------------------------------	--

TLV (USA)	Long-term value: 0,0001* mg/m ³ Skin; (SEN) NIC-DSEN, RSEN;* inh. fraction
EL (Canada)	Long-term value: 0,001 mg/m ³ inhalable, Skin; S
EV (Canada)	Long-term value: 0,001 mg/m ³ as total proteins, inhalable, Skin

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.

· Ingredients with biological limit values:
--

108-88-3 toluene	
-------------------------	--

BEI (USA)	<p>0,02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene</p> <p>0,03 mg/L Medium: urine Time: end of shift Parameter: Toluene</p> <p>0,3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)</p>
-----------	---

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.
Pregnant women should strictly avoid inhalation or skin contact.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

(Cont'd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: **Bead Sealer**

(Cont'd. from page 7)

- **Respiratory protection:**
Not required under normal conditions of use.
For spills, respiratory protection may be advisable.
Use suitable respiratory protective device when high concentrations are present.
Use suitable respiratory protective device when aerosol or mist is formed.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment**
No further relevant information available.
- **Risk management measures**
See Section 7 for additional information.
No further relevant information available.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

· Form:	Liquid
· Colour:	Black
· Odour:	Solvent-like
· Odour threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	99 °C (210 °F)

- **Flash point:** -9 °C (16 °F) (TCC D56)

- **Flammability (solid, gaseous):** Not applicable.

- **Auto/Self-ignition temperature:** 215 °C (419 °F)

- **Decomposition temperature:** Not determined.

- **Self-igniting:** Product is not self-igniting.

(Cont'd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: **Bead Sealer**

(Cont'd. from page 8)

· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1,1 Vol %
Upper:	7,0 Vol %
· Oxidising properties	Not determined.
· Vapour pressure at 20 °C (68 °F):	48 hPa (36 mm Hg)
· Density at 20 °C (68 °F):	0,87 g/cm ³ (7,26 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	721 mm ² /s (Converted from <u>5 Zahn</u>)
VOC content:	89,1 %
VOC (California)	75-90 % Wt
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Used empty containers may contain product gases which form explosive mixtures with air.
Flammable.
Reacts violently with oxidising agents.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
Toxic fumes may be released if heated above the decomposition point.
- **10.4 Conditions to avoid**
Keep ignition sources away - Do not smoke.
Store away from oxidising agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Carbon dioxide
Carbon monoxide

(Cont'd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: **Bead Sealer**

(Cont'd. from page 9)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

142-82-5 heptane

Oral	LD50	> 5000 mg/kg (rat) (Estimate)
Inhalative	LC50/4 h	103 mg/l (rat)

1333-86-4 Carbon black

Oral	LD50	10000 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Slight irritant effect on eyes.
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Acute effects (acute toxicity, irritation and corrosivity):**
Causes skin and eye irritation.
Vapours have narcotic effect.
- **Repeated dose toxicity:** Repeated exposures may result in skin and/or respiratory sensitivity.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
Suspected of damaging the unborn child. Route of exposure: Inhalation.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** Toxic for aquatic organisms
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.

(Cont'd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: **Bead Sealer**

(Cont'd. from page 10)


- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Avoid transfer into the environment.
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Contact waste processors for recycling information.
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** UN1133
- **14.2 UN proper shipping name**

	Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).
<ul style="list-style-type: none"> · DOT · ADR · IMDG · IATA 	Adhesives 1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS ADHESIVES, MARINE POLLUTANT ADHESIVES

(Cont'd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: **Bead Sealer**

(Cont'd. from page 11)

· **14.3 Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids.
· **Label** 3

· **ADR**



· **Class** 3 (F1) Flammable liquids.
· **Label** 3

· **IMDG**



· **Class** 3 Flammable liquids.
· **Label** 3

· **IATA**



· **Class** 3 Flammable liquids.
· **Label** 3

· **14.4 Packing group**

· **DOT, ADR, IMDG, IATA** II

· **14.5 Environmental hazards:** Product contains environmentally hazardous substances: heptane

· **Marine pollutant:** Yes

· **Special marking (ADR):** Symbol (fish and tree)

· **Special marking (ADR):** Symbol (fish and tree)

· **14.6 Special precautions for user** Warning: Flammable liquids.

· **Danger code (Kemler):** 33

· **EMS Number:** F-E,S-E

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

(Cont'd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: **Bead Sealer**

(Cont'd. from page 12)

· Transport/Additional information:	
· ADR	
· Transport category	2
· Tunnel restriction code	D/E
· IATA	
	Limited quantity by air: 1L
· UN "Model Regulation":	
	UN 1133 ADHESIVES, 3, II

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **United States (USA)**

· **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
----------	---------

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65 (California):**

· **Chemicals known to cause cancer:**

References to chemical components listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

1333-86-4	Carbon black
-----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3	toluene
----------	---------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

· **Carcinogenic Categories**

· **EPA (Environmental Protection Agency)**

108-88-3	toluene	II
----------	---------	----

142-82-5	heptane	D
----------	---------	---

· **IARC (International Agency for Research on Cancer)**

1333-86-4	Carbon black	2B
-----------	--------------	----

990001-01-0	toluene	3
-------------	---------	---

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
-----------	--------------

(Cont'd. on page 14)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: **Bead Sealer**

(Cont'd. from page 13)

· **Canada**· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

108-88-3 toluene

142-82-5 heptane

· **Directive 2012/18/EU**· **Named dangerous substances - ANNEX I**

None of the ingredients are listed.

· **Other regulations, limitations and prohibitive regulations**· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients are listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child. Route of exposure: Inhalation.

H373 May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

(Cont'd. on page 15)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA
GHS

Printing date 13.11.2015

Revision: 13.11.2015

Trade name: Bead Sealer

(Cont'd. from page 14)

LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B
Repr. 2: Reproductive toxicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Sources

SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com