Safety Data Sheet

Issue Date: 09-Jul-2015 Revision Date: 24-Jun-2020 Version 1

1. IDENTIFICATION

Product identifier

Product Name Flammable Rim Sealant, Flammable Rim Sealant Extra Thick, Flammable Bead Sealer,

Bead Leak Sealer

Other means of identification

SDS # ELG-010

Product Code Catalog numbers: 1-795, 1-770, 1-797, 1-771, 1-772, 1-773, 2-795, 2-770, 2-797, 2-771, 2-

772, 2-773, 4-795, 4-770, 4-797, 4-771, 4-772, 4-773, 1-797, 1-777, 1-740, 1-778, 1-779, 2-797, 2-777, 2-740, 2-778, 2-779, 4-797, 4-777, 4-740, 4-778, 4-779, BS32, BSG, BS5G,

CH40, CH43, WCH40, WCH43, BL

UN/ID No UN1133

Recommended use of the chemical and restrictions on use

Recommended Use Rubber adhesive.

Details of the supplier of the safety data sheet

Supplier Address

ELGI Rubber Company, LLC 600 N. Magnolia Ave. Luling, TX 78648

Ph: 830-875-5539

Emergency telephone number

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Black high viscosity liquid Physical state Liquid Odor Petrolic

Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Signal Word

Danger

Hazard statements

Causes skin irritation Suspected of causing cancer

May be fatal if swallowed and enters airways

May cause respiratory irritation. May cause drowsiness or dizziness

Highly flammable liquid and vapor





Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed Ground/bond container and receiving equipment

Use explosion-proof equipment Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

<u>Precautionary Statements - Response</u>

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a poison center or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Very toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
N-Heptane	142-82-5	80-90
Carbon Black	1333-86-4	0-5

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST AID MEASURES

Description of first aid measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. If skin irritation occurs: Get medical advice/attention. Wash

Revision Date: 24-Jun-2020

contaminated clothing before reuse.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

poison center or doctor/physician if you feel unwell.

Ingestion Do NOT induce vomiting, Immediately call a poison center or doctor/physician. If vomiting

occurs naturally, have victim lean forward to reduce risk of aspiration.

Most important symptoms and effects, both acute and delayed

Symptoms Causes skin irritation. May be harmful in contact with skin. May cause drowsiness or

dizziness. May cause pulmonary edema. Possible symptoms are irritation of the mucous membranes, dry cough and respiratory difficulty. Other symptoms may include dizziness,

headache, nausea, and loss of coordination.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Aspiration of material into the lungs due to vomiting can cause

chemical pneumonitis which can be fatal. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to high concentrations of hydrocarbon solvents. The use of other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs are administered, observe for the development of cardiac

arrhythmias.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray (fog). Alcohol resistant foam. Dry chemical. Carbon dioxide (CO2).

Unsuitable Extinguishing Media Do not use solid water streams.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. The liquid vapor may settle into low areas or may travel along the ground or surface to ignition sources where they might ignite or explode. Flash back possible over considerable distance.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2).

Explosion Data

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool. Fight fire remotely due to the risk of explosion.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet. Evacuate

personnel to safe areas. Remove all sources of ignition. Ensure adequate ventilation. Avoid

breathing vapors or mists.

Environmental precautions

Environmental precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See

Section 12, Ecological Information.

ELG-010 - Flammable Rim Sealant, Flammable Rim Sealant Extra Thick, Flammable Bead Sealer, Bead Leak Sealer

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an inert

(i.e. vermiculite, dry sand or earth) absorbent material.

Methods for Clean-UpUse only non-sparking tools. Place in properly labeled, sealed, non-leaking containers.

Dispose of contents/container via a licensed waste disposal contractor. For waste disposal,

Revision Date: 24-Jun-2020

see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Wash face, hands and any exposed skin thoroughly after handling. Wear protective

gloves/protective clothing and eye/face protection. Avoid breathing

dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use spark-proof tools and explosion-proof equipment. Take

precautionary measures against static discharges. Keep cool.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Store locked up. Heat

sensitive-store under inert gas.

Incompatible Materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-Heptane	STEL: 500 ppm	TWA: 500 ppm	IDLH: 750 ppm
142-82-5	TWA: 400 ppm	TWA: 2000 mg/m ³	Ceiling: 440 ppm 15 min
		(vacated) TWA: 400 ppm	Ceiling: 1800 mg/m ³ 15 min
		(vacated) TWA: 1600 mg/m ³	TWA: 85 ppm
		(vacated) STEL: 500 ppm	TWA: 350 mg/m ³
		(vacated) STEL: 2000 mg/m ³	
Carbon Black	TWA: 3 mg/m ³ inhalable	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³
1333-86-4	particulate matter	(vacated) TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³
			TWA: 0.1 mg/m ³ Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits. Showers

Eyewash stations

Ventilation systems. Explosion-proof general and local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear goggles or chemical safety glasses. Refer to 29 CFR 1910.133 for eye and face

protection regulations.

ELG-010 - Flammable Rim Sealant, Flammable Rim Sealant Extra Thick, Flammable Bead Sealer, Bead Leak Sealer

Skin and Body Protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

N-butyl acetate

Not applicable

(Air=1)

Revision Date: 24-Jun-2020

If necessary, wear a MSHA/NIOSH-approved respirator. Refer to 29 CFR 1910.134 for **Respiratory Protection**

respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance Black high viscosity liquid Petrolic Odor

Color Black **Odor Threshold** Not determined

Values Remarks • Method **Property**

Not determined Hq

Melting point / freezing point -90.0 to -90.1 °C / -131.7 to -130.3

Boiling point / boiling range 98.1 to 98.7 °C 208.5 to 209.6 °F

Flash point -4.0 °C / 24.8 °F

Evaporation Rate

Flammability (Solid, Gas) Not determined

Flammability Limit in Air

Upper flammability or explosive 7%

limits

Lower flammability or explosive 1.1%

limits

Vapor Pressure 110.7 hPa (83.0 mmHg) at 37.7 °C

(99.9°F), 53.3 hPa (40.0 mmHg) at

20.0 °C (68.0°F)

Vapor Density 3.30

Relative Density 0.684 g/mL at 25°C (77°F)

Water Solubility Not determined

Solubility in other solvents Insoluble **Partition Coefficient** log Pow > 3.000 **Autoignition temperature** 223.0 °C / 433.4 °F **Decomposition temperature** Not determined Kinematic viscosity Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

Other information

Molecular weight 100.2 g/mol

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

ELG-010 - Flammable Rim Sealant, Flammable Rim Sealant Extra Thick, Flammable Bead Sealer, Bead Leak Sealer

Revision Date: 24-Jun-2020

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes.

Skin Contact Causes skin irritation. May be harmful in contact with skin.

Inhalation May cause drowsiness or dizziness. May cause irritation to the mucous membranes and

upper respiratory tract.

Ingestion May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea,

diarrhea, and vomiting.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50		
N-Heptane 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m³(Rat)4 h		
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg(Rabbit)	-		

Symptoms related to the physical, chemical and toxicological characteristics

Please see section 4 of this SDS for symptoms. **Symptoms**

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Carbon black is a possible carcinogen when it appears as a respirable dust.

Chemical name	ACGIH	IARC	NTP	OSHA
Carbon Black	A3	Group 2B		X
1333-86-4		·		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans
OSHA (Occupational Safety and Health Administration of the US Department of Labor)

STOT - single exposure May cause drowsiness or dizziness.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

Dermal LD50 3,158.00 mg/kg ATEmix (inhalation-dust/mist) 114.00 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
N-Heptane		375.0: 96 h Cichlid fish mg/L LC50	10: 24 h Daphnia magna mg/L
142-82-5			EC50
Carbon Black			5600: 24 h Daphnia magna mg/L
1333-86-4			EC50

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
N-Heptane	4.66
142-82-5	

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Whatever cannot be saved for recovery or recycling should be managed in an appropriate

and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance

with federal, state and local requirements.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status		
N-Heptane	Toxic		
142-82-5	Ignitable		

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT

UN/ID No UN1133
Proper Shipping Name Adhesives

Hazard class 3
Packing Group II

IATA

UN number UN1133
Proper Shipping Name Adhesives

Transport hazard class(es) 3
Packing Group ||

IMDG

UN number UN1133
Proper Shipping Name Adhesives

Transport hazard class(es) 3
Packing Group || Marine Pollutant Yes

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
N-Heptane	Х	ACTIVE	Х	Х	Х	Х	X	Х	Х
Carbon Black	Х	ACTIVE	Х	Х	Х	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65	
Carbon Black - 1333-86-4	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical name		New Jersey	Massachusetts	Pennsylvania	
	N-Heptane 142-82-5	Х	X	X	
	Carbon Black 1333-86-4	Х	X	X	

16. OTHER INFORMATION

NFPA_	Health Hazards	Flammability	Instability	Special Hazards
	1	3	0	Not determined
HMIS_	Health Hazards	Flammability	Physical hazards	Personal Protection
	1	3	0	Not determined

 Issue Date:
 09-Jul-2015

 Revision Date:
 24-Jun-2020

Revision Note: SDS sections updated

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet